

# Index

## Symbols

? (question mark)

- Ethernet commands and 2-19
- Frame Relay commands and 4-25, 5-29
- local commands and 1-8, 1-14
- subinterfaces and 4-25, 5-29

## Numerics

- 0.0.0.0 IP addresses, ACLs and 13-5
- 0.0.0.0 routes, security associations and 12-47
- 165.165.100.100 (VR for control VPN) 2-21
- 165.165.100.99 (VR for control VPN) 2-21

## A

- AAL mode (ATM adaptation layers mode) 6-17
- AAL1 mode 6-18
- AAL5 mode 6-17
- abbreviations of commands 1-17–1-18, 3-2
  - commit 2-10
  - display 2-10
  - display tabular 4-3
  - ds-byte-filter 7-26
  - encapsulation 4-33
  - local-isakmp-identity command keyword 12-38
- abort command 1-16
- ABR (available bit rate) setting 6-18
  - PCR and MCR and 6-22
  - quality of service 6-28
- ABRs (area border routers)
  - OSPF and 10-5
- access blades
  - see also* Ethernet, channelized DS3, channelized E3, OC-3
  - control VRs and 1-23
  - SNMP and 1-23
  - specifying slot number 2-7
  - subscriber VRs and 1-23, 2-4, 2-5
  - VRs and 2-6
- access devices, Frame Relay. *see* FRAD (Frame Relay access devices)
- access-lists 13-44
  - see also* NAT (network address translation)
  - ACLs versus 13-47
  - command examples 13-47
  - end address keyword 13-47
  - access-lists (*continued*)
    - list ID keyword 13-47
    - permit keyword 13-47
    - start address keyword 13-47
    - VI ID keyword 13-47
  - accounting servers, RADIUS 13-51
  - ACL (setting) 7-6, 7-8, 7-11, 13-9
  - ACLs (access control lists)
    - see also* export policies, import policies
    - access-lists versus 13-47
    - advantages of 7-4
    - changing values in 7-7
    - CLI level for 7-22
    - creating 7-4–7-7
      - command for 7-7
      - for diff-serve 7-20–7-25
    - crypto map and 12-28
    - default IP addresses in 13-5
    - destination address 7-6
    - destination UDP protocol port 7-6
    - diff-serve and 7-26
      - identifying 7-27
    - diff-serve and QoS and 7-17
    - dstaddr and 8-17
    - example 7-7
    - export policies and 7-4, 7-8, 7-11
    - firewalls and 13-4
    - for IPSec transport mode 12-29
    - GALs (general access lists) and 13-5
    - import and export policies and 8-13
    - import policies and 7-4, 7-8
    - in IPSec 12-9
    - installing in crypto maps 12-28
    - IPSec-manual crypto map and 12-29
    - packet filters and 13-10
      - destination address 13-6
      - destination UDP protocol port 13-6
      - port settings 13-6
      - required values 13-5
      - source address 13-6
      - source UDP protocol port 13-6
      - transport protocol port 13-6
    - reusing 13-8
    - settings
      - ACL 7-6
      - dstaddr 7-6

- ACLs (access control lists) (*continued*)
    - settings
      - dstport 7-6
      - protocol 7-6
      - srcaddr 7-6
      - srcport 7-6
      - TOS 7-6
      - VPN 7-6
      - VR 7-6
    - source address 7-6
    - source UDP protocol port 7-6
    - TCP/UDP ports 13-6
    - tips and techniques 7-7
    - traffic conditioners and 7-17
    - transport protocol port 7-6
    - types of service 7-6
  - action setting 7-8, 7-11
    - firewall access tables 13-13
  - address setting 12-14
  - address translation
    - proxy servers and 13-15
  - adjacencies
    - enabling event logging 9-27
    - init values and 9-19
    - IS-IS 9-19
  - admin status setting
    - OC-3c 6-7
  - admin-status setting 2-20, 5-45
    - enable setting and
      - DS3 5-28, 5-32
      - E3 4-24, 4-29
  - affinity (option) 11-16
  - agent, SNMP 2-21
  - aggregates, creating 10-13
  - aggressive-mode (crypto map flag value) 12-28
  - AH
    - authentication algorithms 12-7
    - characteristics 12-7
    - IPSec and 12-7
  - ah-md5-hmac keyword 12-22
  - ah-rfc1828 mode 12-22
  - ah-sha-hmac keyword 12-22
  - AIS (alarm indication signals), OC-3c and 6-15
  - AIX, IBM 1-2
  - alarm setting 6-6
  - alarms
    - see also* individual alarm names and messages
    - DS3 5-10
    - DS3 connections 5-7
    - E3 4-3
      - performance monitoring 4-3
    - messages 5-10
      - DS3 5-10
        - enabling and disabling 5-9, 6-6
    - OC-3c 6-6
  - alarms (*continued*)
    - SONET 6-7
  - alert messages, viewing 2-23
  - algorithms, authentication. *see* authentication algorithms
  - alignment, secure multiframe 5-3
  - align-signal setting 4-7
  - always-on connectivity, PVCs and 6-2
  - always-plain (crypto map flag value) 12-28
  - AMI (alternate mark inversion) 5-2
    - see also* line code
  - announce isis option 11-26
  - ANSI
    - DS1/DS3 connectivity standards, support for 5-3
    - line management format 4-17, 5-20
  - ANSI Annex-D 4-17, 5-20
  - ANSI LMI 4-12, 4-22, 5-15, 5-25
    - see also* Frame Relay
  - anti-clogging 12-14
  - any (default value) 7-15
  - AOL
    - proxy 13-36
    - UDP port 13-37
  - append-after setting 11-8
  - application gateways 13-11
    - see also* proxy servers
  - area addresses, IP networks and 9-5
  - area aggregate setting 10-13
  - area range setting 10-7, 10-13
  - area setting 10-5
    - area border routers and 10-5
  - area-address setting 9-4, 9-5
  - area-password setting 9-10
  - areas, stub 10-5
    - area aggregate setting 10-13
    - default cost setting 10-13
- AS (autonomous system) 8-7
  - confederations. *see* confederations
  - IGPs and 7-35
  - IS-IS 9-15
  - neighbor command and 8-11
  - numbers 7-35
    - see also* BGP-4
    - private 8-21
  - traffic 8-15
- ASBRs (autonomous system border routers)
  - configuring OSPF as 10-15
- ATM (asynchronous transfer mode)
  - see also* OC-3c
  - AAL1 6-18
  - AAL5 6-27
  - AAL5 mode 6-17
  - adaptation layers 6-17
  - blades, accessing 6-3
  - classes of service 6-17

- ATM (asynchronous transfer mode) *(continued)*
  - configuring 6-2, 6-8–6-13
    - ILMI and 6-9
    - important settings 6-11
  - connectionless data transfers 6-17
  - CPCS 6-27
  - ILMI 6-8, 6-27
    - importance of using default values 6-11
    - traffic 6-10
    - version 6-10
  - IPoATM 6-26
    - enabling 6-34
  - IPSX switches and 6-18
  - Japanese networks 6-6
  - LAN emulation (LANE) 6-8
  - naming the interface 6-9
  - NNIs 6-8
  - nomenclature 6-9
  - operation and management (OAM) 6-19
  - over DS3 6-33
  - PPPoATM. *see* PPPoATM (PPP over ATM)
  - QoS. *See* QoS (quality of service)
  - segmentation and reassembly sublayer (SAR) 6-17, 6-21
  - service-category setting 6-17
  - settings
    - IF-name 6-9
    - ILMI version 6-10
    - ILMI-VCI 6-10, 6-11
    - ILMI-VPI 6-10, 6-11
    - maximum burst size (MBS) 6-21
    - maxvci-bits 6-10, 6-11
    - maxvc-number 6-10
    - maxvpi-bits 6-9, 6-11, 6-12
    - maxvp-number 6-10
    - neighbor-IP-address 6-10
    - neighbor-name 6-10
    - UNI type 6-10
    - UNI version 6-10
  - SNMP
    - service data units containing ILMI signals 6-27
  - SONET. *see* SONET (synchronous optical network)
  - subinterface configuration. *see* ATM subinterface configuration
  - traffic contracts 6-16
  - traffic descriptors 6-21
  - UNIs 6-8
  - values, viewing 6-11
  - VCI and VPI 6-2
  - VCI minimum value 6-22
  - virtual channel circuits
    - maximum number of 6-11
  - virtual paths 6-2
    - maximum number of 6-11
- atm enable command 6-7
- ATM Forum UNI 4.0 specification 6-8
- ATM subinterface configuration 6-19–6-30
  - AAL5 CPCS 6-27
  - bandwidth considerations 6-20
  - cell rates
    - calculating 6-28
    - default 6-24
    - initial, dynamic bandwidth allocation 6-26
    - minimum 6-26
    - peak 6-21
    - sustained 6-21
  - creating 6-21
  - criteria 6-32
  - dynamic bandwidth allocation 6-26
  - encapsulation types
    - LLC encapsulation 6-27
    - VC-multiplex-routed 6-27
  - IPoATM enabled by default 6-25
  - logical interfaces 6-31
  - OAM ping test 6-26
  - PCR and UBR 6-22
  - PPPoATM. *see* PPPoATM (PPP over ATM)
  - PVC types 6-27
  - QoS/service-category dependence 6-21
  - service categories. *see* service categories
  - settings
    - connection-kind 6-26
    - encapsulation 6-27
    - initial cell rate (ICR) 6-23, 6-26
    - maximum burst size (MBS) 6-23, 6-26
    - minimum cell rate (MCR) 6-21
    - OAM-loopback 6-26
    - peak cell rate (PCR) 6-21, 6-23, 6-26
    - PVC-type 6-27
    - service-category 6-22, 6-27
    - sustained cell rate (SCR) 6-21, 6-27
    - VCI 6-28
    - VCI as local channel identifier 6-28
    - VPI 6-28
  - VCCs/VCI start at 33 6-21
  - VCI and VPI combined 6-28
  - viewing default settings 6-22
  - VIs and 6-30
    - connecting 6-30
- AUTH (authentication) area, PPP and 4-30, 5-33
- authentication (ISAKMP policy setting) 12-18
- authentication (setting) 5-32
  - DS3 5-28, 5-32
  - E3 4-24, 4-29
  - L2TP PPP 14-10
  - L2TP tunnels 14-11
  - OC-3 POS 6-44
  - PPPoATM 6-36
  - PPTP and 13-57
  - reauth setting and 4-24

### authentication algorithms

*see also* IPsec

#### chapmd5

- in HDLC channels 4-29, 5-32
- in PPP over ATM 6-36
- in PPP over Frame Relay 4-24, 5-28
- in PPP over OC-3 POS 6-44
- in PPTP 13-57
- PPTP and 13-58

#### ISAKMP policies 12-18

- pre-shared key 12-18
- rsa-sig 12-18
- XAUTH explained 12-18
- xauth-init-preshared 12-18
- xauth-init-rsa-sig 12-18

#### MD5 12-3, 12-7, 12-11

- activating 9-10
- for anti-clogging 12-15
- in BGP neighbor routing 8-10
- in crypto transform-sets 12-11, 12-22
- in ISAKMP policies 12-18
- in IS-IS domain passwords 9-10
- in OSPF 10-12

#### mschapv1

- in HDLC channels 4-29, 5-32
- in PPP over ATM 6-36
- in PPP over Frame Relay 4-24, 5-28
- in PPP over OC-3 POS 6-44
- in PPTP 13-57

#### pap

- in HDLC channels 4-29, 5-32
- in PPP over ATM 6-36
- in PPP over Frame Relay 4-24, 5-28
- in PPP over OC-3 POS 6-44
- in PPTP 13-57

#### SHA-1

- for anti-clogging 12-15
- in crypto transform-sets 12-11, 12-22
- in ISAKMP policies 12-18

#### xauth

- ISAKMP and 12-18

authentication of passwords. *see* password verification

authentication servers, RADIUS 13-51

auto-detect setting 4-4, 5-7

autoneg setting 2-20, 3-4

autoroute announce setting 11-4, 11-12

autoroute metric relative setting 11-13

autoroute metric setting 11-4, 11-12

autoroute setting

- announce isis option 11-26
- metric relative option 11-26
- MPLS tunnels and 11-26

## B

B8ZS (binary eight zero substitution) 5-2

- DS3 and 5-9
- requirements 5-13

back-to-back configuration 4-26

bandwidth

- Frame Relay VIs 4-13, 5-16
- minimum, assigning to a subinterface 4-22, 5-25
- MPLS tunnels and 11-16
- overprovisioning, avoiding 11-21
- statistical 4-11

bandwidth (option) 11-16

bandwidth (setting) 11-13

Bc (committed burst size) setting

- see also* subinterfaces
- Be setting and 4-21, 5-24
- CIR setting and 4-21, 4-28, 5-24, 5-31
- modifying CIR bandwidth 5-25
- DS3 5-16, 5-23
- E3 4-13, 4-20
- for FRoIP DLCI 5-47
- unchannelized DS3 and 5-38
- unchannelized E3 and 4-35

BDRs (backup designated routers) 10-11

- IS-IS and 9-15

Be (excess burst size) setting

- see also* subinterfaces 4-22
- Bc setting and 4-21, 5-24
- CIR setting and 4-21, 5-24
- DS3 5-16, 5-23
- E3 4-13, 4-20
- for FRoIP DLCI 5-47
- unchannelized DS3 and 5-38
- unchannelized E3 and 4-35

BECN (backward explicit congestion notification) 4-11, 5-14

- dropped frames and 4-12, 5-15

best-effort tunnels 11-3, 11-13

- configuring 11-24
- defining behavior of 11-26
- recording tunnel route 11-17

#### BGP

- OSPF and 7-11

BGP community attribute

- custom values in 8-26
- defined in export policies 7-12
- export policies 8-25
  - number of communities 8-26
- import policies 8-25
  - creating 8-25
- in confederations 8-23
- in route policies 7-4
- no-advertise option 8-25, 8-26
- no-advertise value 7-12
- no-export option 8-25, 8-26

- BGP community attribute (*continued*)
  - no-export value 7-12, 8-23, 8-27
  - no-export-sub option 8-25
  - preventing exportation of internal BP routes 7-16
  - proprietary values 7-12
  - RFC 1998 standard values 8-27
  - route coloring 8-25
  - settings, BGP-community 7-8
  - using for route filtering 8-27
- bgp confederation command 8-4
- bgp confederation peers command 8-5
- bgp dampening command 8-6
  - options 8-6
- bgp default-metric command 8-4
- BGP-4 routing 8-1–8-33
  - BGP community attribute. *see* BGP community attribute
  - BGP keepalive time 8-12
  - commands 8-4
    - bgp confederation 8-4
    - bgp dampening 8-6
    - bgp default-metric 8-4
    - neighbor. *see* neighbor command
    - network 8-13
  - community
    - viewing 8-33
  - configuring 8-2
    - minimum configuration 8-2
    - viewing configuration 8-33
  - event logging 8-32
  - export policies and 8-3
  - exporting local routes into 8-2
  - IETF routing protocol RFCs and 7-2
  - import policies
    - using 8-3
  - ISP VRs and 1-23, 8-3
  - local-pref
    - in routing tables 7-37
  - local-preference attribute 8-7
    - I-BGP peers and 8-7
    - traffic and 8-15
  - meshes 8-20
  - multi-exit discriminator (MED) 8-3, 8-7
    - applied to incoming traffic 8-15
    - differences from Cisco 7-16
    - in routing tables 7-37
  - neighbors. *see* neighbor command
  - password capability 8-10
  - placement in ISP VRs 7-35
  - reliability, enhancing 8-18
  - route dampening 8-5, 8-6
    - half-life 8-6
    - max-suppress metric 8-6
    - suppress limit 8-6
  - route injection and 8-3
  - route reflection. *see* route reflection
- BGP-4 routing (*continued*)
  - settings, default-local-pref 8-17
  - states
    - active 8-30
    - connect, active, and idle 8-30
    - established 8-30
    - idle 8-30
    - opensent 8-30
    - subscriber VRs and 8-3
    - troubleshooting 8-30
  - BGP-AS setting 7-11
  - BGP-community (setting) 7-8, 7-12
  - bit stuffing, DS3s and 5-7
  - blades
    - access, FRoIP 5-50
    - control. *see* control blades
    - Ethernet. *see* Ethernet blades
    - processor. *see* processor blades
    - unchannelized, bandwidth 5-50
  - block ciphers 12-6
  - boot configuration
    - see also* initial configuration
    - changing
      - during operation 1-7
      - during startup 1-3
    - commands 1-5–1-6
      - bootfile 1-4, 1-5
      - checkpasswd 1-5, 1-10, 1-11
      - configfile 1-6
      - done 1-6
      - during an interrupted restart 1-4
      - gateway 1-5
      - help 1-3, 1-5
      - host 1-5
      - keep-image 1-9
      - netmask 1-5
      - port 1-5
      - question mark (?) 1-8, 1-14
      - reboot 1-9
      - savefile 1-6
      - target 1-5
      - viewing a list of 1-3
      - wait 1-6, 1-7
      - watchdgenab 1-6
    - displaying current configuration 1-7
    - ending 1-6
    - example 1-5, 1-6
    - flash memory
      - booting from 1-5
      - using 1-6, 1-8, 1-9
    - image file configuration paths 1-4
    - managing 1-3
    - modifying 1-9
    - problems, administrator login and 1-10
    - setting up 1-2

- boot configuration (*continued*)
    - settings 1-8
      - bootcfg 1-8
      - bootfile 1-8
      - changing 1-6
      - configfile 1-8
      - gateway 1-8
      - host 1-8
      - port 1-8
      - savefile 1-8
      - target 1-8
    - TFTP host 1-5, 1-8
    - watchdog timer 1-6
  - boot images
    - directory path 1-8
    - in flash memory 1-9
    - new, caution 1-2
  - bootcfg
    - closing 1-6
    - prompt 1-3
      - obtaining 1-2
  - bootcfg (setting) 1-8
  - Bootcfg listing 1-8
  - bootfile command 1-4, 1-5
  - bootfile setting 1-8
  - BOOTP, flag required for IPsec 12-28
  - Bootstrap protocol client port 13-7
  - border routers 10-4
  - BPV (bipolar violations). *see* line code
  - buffered packet sequence, FRoIP, length of 5-45
- C**
- CA (certificate authority). *see* certificates
  - cablelength setting 5-7
  - cables, length of (DS3) 5-7
  - Can not set object 5-26, 5-50
    - ATM settings and 6-12
    - crypto maps and 12-28
    - firewall access tables and 13-12
    - IGPs and 7-16
    - import policy values and 7-10
    - RIP 7-38
  - c-bit framing standard
    - c-bit path code violations 5-10
    - c-bit path errored seconds 5-10
    - c-bit path severely errored seconds 5-10
  - c-bit path code violations 5-10
  - c-bit path errored seconds 5-10
  - c-bit path severely errored seconds 5-10
  - c-bit setting 5-7
  - CBR (constant bit rate) setting 6-18
  - CCITT Q933 LMI 4-12, 5-15
  - CCV alarm 5-10
  - cell rates
    - ATM subinterfaces, default 6-24
    - calculating 6-28
    - service category and 6-21
  - certificate configuration level 12-11
  - certificates
    - see also* IPsec
    - certificate authority, functions performed 12-9
    - exchange process 12-9
    - installing through the CLI 12-38
    - IRE dial-up clients and 12-35
    - public/private key pair 12-9
    - using a text editor with the CLI 12-38
    - with IPsec-Dialup crypto maps 12-38
  - CES alarm 5-10
  - challenge handshake authentication protocol (CHAPMD5).
    - see* authentication algorithms
  - channel 0 5-36
    - unchannelized DS3 and 5-36
    - unchannelized E3 and 4-33
  - channel command 5-11
    - example 4-9
    - options 5-12
  - channel groups. *see* DS3, E3
  - channel-level link protocol, commands for 4-23, 5-27
  - channels 5-3
    - see also* DS3, E3
    - channel banks 5-3
    - commands
      - channel command 5-11
      - channel command options 5-12
    - DS3 example 5-12
    - E3 blades and 4-8–4-10
    - FTP command and data 13-8
    - host, serial interfaces and 4-14, 5-16
    - size 5-11
    - viewing list of 5-13
  - CHAPMD5 (challenge handshake authentication protocol).
    - see* authentication algorithms
  - checkpasswd command 1-5, 1-10, 1-11
  - Cheswick & Bellovin, *Firewalls and Internet Security* 13-4
  - child-limit setting 13-16, 13-23
    - plug proxies and 13-34
    - Telnet proxies 13-36
  - CIDR (classless interdomain routing) 2-3
  - ciphers, block 12-6
  - CIR (committed information rate) setting 4-20, 5-23
    - see also* subinterfaces
    - bandwidth, Bc value and 5-25
    - Bc and Be settings and 5-24
    - Bc setting and 4-21, 4-28, 5-31
    - Be setting and 4-21
    - DS3 and 5-16
    - E3 and 4-13
    - Frame Relay and 4-11, 5-14

- CIR (committed information rate) setting (*continued*)
  - Frame Relay subinterfaces and 4-18, 5-21
  - for FRoIP DLCI 5-47
  - unchannelized DS3 and 5-38
  - unchannelized E3 and 4-35
- circuits, virtual. *see* PVCs (permanent virtual circuits)
- circuit-type setting 9-8
  - IS-IS routing and 9-4
- Cisco
  - CPE router 10-13
  - diff-serve and 7-17
  - E3 modules 4-7, 4-31
  - Frame Relay
    - frame-relay setting 4-15, 5-18
  - HDLC
    - E3 and 4-10
    - encapsulation type 5-17
    - MPLS and 11-3
  - interoperability with IPSec 12-8, 12-20
  - interoperability with OC-3 POS 6-39
  - IOS 7-2
    - MPLS tunnels and 11-27
  - IS-IS and 9-4
    - timer commands 9-11
  - MED 7-16
  - OSI layer 2 protocol HDLC 4-36, 5-39
  - OSPF link-state database 10-17
- Cisco (line management format) 4-17, 5-20
- Cisco LMI (local management interface). *see* Frame Relay
- Cisco LMI setting 4-12, 5-15
- Cisco routers and IPSec
  - hex and ASCII manual key values 12-34
  - interoperability 12-8
  - ISAKMP lifetime settings 12-20
- classes of service (ATM) 6-17
- clear channel capability 5-2
  - see also* line code standards
- DSOs and 5-13
- CLI
  - command levels
    - ATM 6-11
    - DLCI 5-46
    - FRAME-RELAY 4-14, 5-17
    - l2tp 14-8
    - map 12-29
    - OSPF router 10-19
    - PPP 4-30, 5-33
    - router BGP 8-17
    - serial PPP 6-36
    - session submenu 14-8, 14-10
    - tunnel submenu 14-8, 14-10
    - VR 7-7
  - commands, entering 1-12
  - configurations, InVision SMS and 1-7
  - CLI (*continued*)
    - prompt, commands and 1-13
  - clients, remote
    - enabling use of IPSec 12-26
  - CLNP (connectionless network protocol) packets 9-1
  - clock (setting)
    - DS3 5-7
    - E3 4-4
    - OC-3c 6-5
    - unchannelized E3 4-32
  - CO (Central Office) 6-33
  - commands
    - see also* individual command and setting names
    - abbreviations. *see* abbreviations of commands
    - cancelling 1-16
    - CLI prompt and 1-13
    - global 1-13
    - help 1-14
    - keywords and 1-14
    - local 1-13
      - question mark (?) and 1-8, 1-14
    - navigating through the CLI hierarchy 1-16
    - obtaining specific information on 1-14
    - operation modes and 1-13
    - syntax 1-14
    - types of 1-12
  - commit command 1-16
    - abbreviations 2-10
    - config command and 1-15
    - shutdown command and 4-7, 5-5
    - SNMP and 2-22
    - VR creation and 2-6
  - committed burst size (Bc). *see* Bc (committed burst size)
    - setting
  - committed information rate (CIR). *see* subinterfaces
  - communities. *see* BGP community attribute
  - community command (SNMP), community strings and 2-24
  - community strings 2-24
    - community command and 2-24
    - snmp enable command and 2-24
    - SNMP hosts and 2-25
    - SNMP, defining 2-22
    - traps hosts and 2-25
  - CompuServe
    - proxy 13-36
    - UDP port 13-37
  - concentration router. *see* route reflection
  - Concentrator, E1 4-1
  - confederations 8-4, 8-20–8-23
    - see also* BGP-4 routing
    - advantages 8-4
    - bgp confederation peers command 8-5
    - disadvantages 8-21
    - E-BGP sessions in 8-21
    - elements of 8-20

- confederations (*continued*)
  - private AS numbers 8-21
  - usage of IGP in 8-23
- config command 1-12
  - abbreviation 2-19
  - navigation tool 1-15
  - show command and 1-18
- config controller command
  - unchannelized E3 and 4-31, 5-34
- configfile command 1-6
- configfile setting 1-8
- config-req-retransmit setting
  - DS3 PPP over Frame Relay 5-28, 5-32
  - E3 PPP over Frame Relay 4-29
  - L2TP PPP 14-10
  - OC-3 POS 6-44
  - PPP over Frame Relay 4-24
  - PPPoATM 6-36
- configuration
  - back-to-back 4-26
  - changes
    - canceling 1-16
    - saving 1-16
  - features, shutting down 1-17
  - files
    - names of 1-8
    - naming 1-6
  - mode, entering 1-12
  - settings, viewing 1-13
  - status, viewing 1-18
  - testing with the keyword no 1-17
  - VRs and VIs and, removing 1-17
- congestion notification 4-11, 5-14
- connected-to command
  - across two VPNs 2-15
  - as a prompt 2-14
  - IPSec tunnel interface 12-40
  - options
    - logical 2-12
    - tunnel 2-12
    - virtual 2-12
  - syntax 2-14
  - to logical interface 2-13
  - using 12-40
  - values required for subinterfaces 2-14
  - VI connections and 2-12, 2-14
    - types of connections 2-14
- connected-to setting, loopback 2-4
- connection-kind setting 6-26
- connectionless IP networks, FRoIP and 5-40
- connections
  - DS3
    - alarms 5-7
  - testing 2-15, 2-17
    - see also* ping command, traceroute command
- constrained shortest path first (CSPF). *see* CSPF (constrained shortest path first)
- contracts, traffic 6-16
- control blades
  - control VRs and 1-23, 2-8
  - Ethernet interfaces
    - specifying which port to use 1-5
    - TFTP download port 1-8
  - Ethernet ports on
    - configuring 2-19
  - firewall access tables and 13-12
  - master control blade
    - ISP and subscriber VRs and 2-5
  - PPTP and 13-11
  - proxies and 13-11
  - subscriber VRs and 1-23
  - syslogD and 13-41
- control VPNs 1-12
  - example 1-25
  - initial configuration and 1-24
  - naming 1-24
  - security strategies 1-26
  - usage guidelines 1-25
  - VRs and 1-24
- control VRs 2-21
  - access blades and 1-23
  - control blades and 1-23, 2-8
  - creating 2-21
    - automatically 2-21
  - loopback VIs and 1-25
  - OSPF and 1-25
  - security strategies 1-26
  - slot numbers and 2-4, 2-5
  - SNMP and 1-23, 2-21
  - SNMP configuration and 2-22
  - VRs 165.165.100.100 and 165.165.100.99 2-21
- controller command
  - channelized E3 and 4-2
  - t3 option 5-4
- controller E3 command, serial interfaces and 4-14, 5-16
- conventions, typographical *xxi*
- corporate networks
  - secure end-user dialup connections for 14-2
- CoSine InGage Customer Network Management Systems* *xxiii*
- CoSine InVision SMS User's Guide* *xxiii*
- CoSine IPSX 9000 Hardware Installation and Reference* *xxii*
- CoSine Technical Assistance Center (TAC) and Web site *xxiii*
- count option 2-16
- CPCS (common part convergence sublayer) 6-27
- CPE router 10-13
- CRC (cyclic redundancy check) 6-6
- crc setting 6-5
  - options for 6-6
- crc-multiframe setting 4-7
- crc-multiframe-febe setting 4-7

- create vr command 2-5
  - cross-connections, checking 6-7
  - crypto command 12-12
  - crypto map 12-12
    - see also* IPsec
    - ACLs
      - using 12-25, 12-28
    - configuration level 12-11
    - creating 12-24–12-39
      - example 12-24
    - enabling remote clients 12-26
    - IKE key command for manual pre-shared keys 12-25
    - IKE-policy command for loading ISAKMP policies 12-25
    - IPsec-manual crypto map. *see* IPsec-manual crypto map
    - ISAKMP policies and transform-sets and 12-24
    - loading transforms 12-25
    - manual keying in 12-29
    - perfect forward secrecy 12-27
      - dependencies and requirements 12-27
    - set command 12-25
    - settings
      - flag 12-25
      - flag, using 12-26
      - IKE key 12-25
      - IKE-policy 12-25
      - local-ISAKMP-identity 12-25
      - match address 12-25
      - PFS-group 12-25
      - transform-set 12-25
      - viewing at the VR level 12-12
    - specifying Diffie-Hellman group 12-25
    - tunnel interfaces and 12-44
  - crypto map flags
    - always-plain 12-28
    - compatibility with BOOTP and DNS 12-28
    - denying a connection 12-27
    - identity-PFS command 12-27
    - PFS value 12-27
    - SA-per-host command 12-27
    - SA-per-net command 12-27
    - SA-per-port command 12-27
    - SA-per-protocol command 12-27
  - crypto map IPsec-ISAKMP configuration level 12-11
  - crypto map IPsec-manual configuration level 12-11
  - crypto transform-set command 12-9
  - crypto transform-set configuration level 12-11
  - CSES alarm 5-10
  - csnp-interval setting 9-11, 9-13
  - CSNPs (complete sequence number protocol data units) 9-16
    - authenticating 9-10
    - intervals between sending 9-11, 9-13
    - LSDB refresh and 9-13
  - CSPF (constrained shortest path first) 11-3
    - defining behavior of 11-12
  - CSPF (constrained shortest path first) (*continued*)
    - dynamic paths and 11-16
    - explicit paths and 11-9
    - MPLS and 11-5
      - MPLS traffic-eng attribute-flags 11-11
  - customer networks, control blades and 2-19
  - customer VRs. *see* subscriber VRs
  - CV\_1 performance counter setting 6-15
  - CV\_p performance counter setting 6-16
  - CV\_s performance counter setting 6-15
- ## D
- D4 format 5-3
  - data framing standards
    - see also* framing standards
    - extended superframe format (ESF) 5-3
    - superframe format (SF) 5-3
  - data links
    - information 5-7
    - T1 5-3
  - data rates
    - maximum, rate-limit command and 2-10
    - setting, rate-limit command and 2-10
  - data sequencing, Frame Relay vs. IP 5-41
  - data theft, preventing. *see* IPsec
  - data transmissions, DS3 and 5-2
  - DCE (network side) interfaces. *see* LMI (local management interface)
  - dce setting 4-16, 5-19
  - DE (discard enable) bit 4-21, 5-24
  - dead-interval setting 10-10
  - dedicated rules table 13-12
  - default cost setting 10-4, 10-13
  - default keyword 7-34
  - default routes in IS-IS 9-5
  - default-info-originate setting 9-5
  - default-local-pref setting 8-17
  - default-metric setting 8-17
  - default-window-size setting 5-43, 5-44
  - default-window-timeout setting 5-43, 5-44
  - defects, OC-3c 6-15
  - delete command 1-17
  - denial-of-service attacks
    - ISAKMP and 12-15
    - stopping 12-14, 12-15
  - deny setting 13-9
  - DES (data encryption standard) 12-6
    - history 12-6
    - specified in ISAKMP policies 12-18
  - destination (setting) 11-14
    - firewall access tables 13-13
  - destination address
    - ACLs 7-6
    - packet filter value 13-6

- destination port
  - ACLs 7-6
  - packet filter value 13-6
- DHCP (dynamic host configuration protocol) relay 13-52
  - dhcp status enable command 13-53
  - displaying settings 13-53
  - enabling or disabling 13-53
  - maxhops setting 13-53
  - RFC 1541 13-52
  - server IP address 13-53
  - threshold timer 13-53
- dhcp status enable command 13-53
- dialup connections, secure 14-2
- Diffie-Hellman group 12-8
  - see also* IPsec
  - crypto map and 12-25
  - example 12-52
  - groups 1, 2, and 5 12-18
  - private key 12-8
- diff-serve 7-17–7-28
  - see also* QoS (quality of service)
  - ACLs and 7-17
    - requirements 7-17
    - specifying 7-28
  - advantages 7-17
  - compatibility with Cisco and Juniper 7-17
  - creating ACLs for 7-20–7-25
  - creating ds-byte-filter rules 7-26
  - filtering TCP/UDP ports 7-26
  - filters
    - default 7-28
    - viewing 7-28
  - firewalls and 7-17
  - help 7-27
  - qos command 7-26
  - RFC 2474 7-17
  - rules
    - configuring 7-26–7-28
    - ID numbers for 7-27
    - priorities 7-26
    - settings for 7-27
    - subscriber VRs 7-30
  - sample network 7-18
  - settings
    - filterID 7-27
    - GenAclID 7-27
    - inbound/outbound 7-27
    - setvalue 7-27
  - subscriber VRs and 7-19
  - support for 7-17
  - use of rules at VR level 7-25
  - used between subscriber and ISP 7-17
  - using, ACLs and 7-26
  - VIs and 7-19
- digital certificates 12-9
  - uses 12-3
- digital signature standard (DSS) algorithm 12-19
- Dijkstra algorithm 9-15
- directories for boot image 1-8
- discard enable (DE) bit 4-21, 5-24
- DISCARDS setting 4-19, 5-22
- display command 1-19
  - abbreviation 1-7
  - channelized E3 and 4-2
  - DS3 and 5-4
  - OSPF and 10-19
  - serial interfaces and 4-14, 5-17
  - tabular option 4-3, 5-5
  - VI settings and 2-8
- display ospf command 10-20
- display route command 7-3
- display stat command 6-41
- display stat sum command 6-41
- display stats command 6-13
- display stats sum command 6-14
- DLCI (CLI command level) 5-46
- DLCI (setting) 5-45
- DLCIs (data link connection identifiers) 4-11, 5-14
  - assigning to subinterfaces 4-22, 5-25
  - available number of, LMI type and 4-17, 5-20
  - defining 4-13, 5-16
  - example 4-13, 5-16
  - Frame Relay configuration and 4-21, 4-27, 5-24, 5-31
  - FRoIP and, creating 5-45
  - FRoIP default-window-timeout setting and 5-43
  - identifying neighboring DLCIs 4-13, 5-16
  - information rate, committed 4-20, 5-23
  - number of
    - LMI type and 4-22, 5-25
  - subinterfaces and 5-28
  - unchannelized DS3 and 5-38
  - unchannelized E3 and 4-35
  - VCI and 6-2, 6-19
- DNS (domain name server)
  - always-plain crypto-map flag required for use with IP-  
Sec 12-28
  - connectivity 13-58
    - dns primary command 13-58
    - dns secondary command 13-58
  - port 13-7
  - proxy servers and 13-11
  - spoofing, rsh and 13-39
- dns primary command 13-58
- dns secondary command 13-58
- domain-password setting 9-10
- done command 1-6
- down state in VIs 6-32
- dr-hello-interval setting 9-11

- 
- DRs (designated routers) 9-9, 10-11
    - Hello PDUs and 9-11
    - IS-IS and 9-15
  - DS0 5-3
    - see also* DS3, HDLC (high-level data link control)
    - bandwidth 5-3
    - channels, viewing list of 5-13
    - clear channel capability and 5-13
    - combining
      - across T1s 5-13
      - in an HDLC channel 5-12
      - in same DS1 5-12
    - fractional T1s and 5-11
    - IPSX and 5-3
    - speed 5-12
    - T1s and 5-2
    - time slots and 5-12
  - DS1
    - bandwidth 5-3
    - data framing formats 5-3
    - DS0s and 5-12
    - IPSX and 5-3
  - DS2
    - bandwidth 5-3
    - tying together 5-7
  - DS3 5-1–5-39
    - see also* E3
    - alarms 5-10
      - see also* alarms
      - displaying 5-5
      - messages 5-10
      - types 5-7
    - alternate mark inversion 5-2
    - bandwidth 5-3
    - bipolar violations 5-2
    - bit stuffing 5-7
    - c-bit framing 5-7
      - alarms 5-10
    - channel configuration options 5-12
      - HDLC ID 5-12
      - speed 5-12
      - T1 ID 5-12
      - time slot 5-12
    - channel groups 5-13
    - channels
      - example 5-12
      - HDLC protocol and 5-3
    - commands
      - controller t3 5-4
      - display 5-4
      - display tabular 5-5
      - show 5-4
    - configuration settings 5-7
      - cablelength 5-7
      - clock 5-7
    - DS3 (*continued*)
      - configuration settings 5-7
        - interface 5-7
      - connectionless networks and 5-40
      - connectivity
        - ANSI standard support 5-3
      - data framing formats
        - defaults 5-9
      - data transmissions and 5-2
      - disabled
        - restoring 5-6
      - disabling 5-5
      - DS0, size of 5-2
      - DS0s and 5-11
      - DS2s and 5-7
      - DSL and 6-33
      - European. *see* E3
      - events 5-10
      - fractional T1s and 5-11
      - Frame Relay and 5-14–5-31
        - see also* Frame Relay
        - overview 5-16
      - framing standards
        - detecting 5-7
      - FRoIP and. *see* FRoIP (Frame Relay over IP)
      - HDLC. *see* HDLC (high-level data link control)
      - interfaces 5-3
        - serial. *see* serial interfaces
        - types, setting 5-19
      - IPSX and 5-3
      - line codes 5-2
      - loopbacks and
        - examples 5-8
        - types 5-8
      - M23 framing 5-7
        - alarms 5-10
      - performance monitoring 5-9–5-11
        - alarms 5-10
      - port monitoring 5-7
        - data 5-5
      - rate policing and 5-24
      - serial interface encapsulation types 5-17
      - serial interfaces. *see* serial interfaces
      - service statistics, viewing 5-5
      - settings
        - auto-detect 5-7
        - c-bit 5-7
        - channel 5-12
        - connection alarms 5-7
        - data link information 5-7
        - default 5-7
        - loopback 5-8
        - M23 5-7
        - status information 5-7
        - test 5-8

DS3 (*continued*)  
  statistics, displaying 5-5  
  T1s and, line code settings 5-9  
  testing, loopback setting and 5-8  
  traffic and 5-8  
  unchannelized. *see* unchannelized DS3  
  using 5-2  
  voice transmissions and 5-2  
  yellow detection and generation 5-9  
DS3U. *see* unchannelized DS3  
DS4 bandwidth 5-3  
DSA algorithm 12-9  
ds-byte-filter command, abbreviation 7-26  
DSL (digital subscriber line) 6-33  
DSLAM (digital subscriber line access multiplier) 6-33  
DSS (digital signature standard) algorithm 12-19  
dstaddr setting 7-6  
  ACLs and 8-17  
  packet filter value 13-6  
  routing policies and 7-4  
dstport setting 7-6  
  packet filter value 13-6  
DTE (user side) interfaces. *see* LMI (local management interface)  
dte setting 4-16, 5-19  
dual loopbacks 4-32  
dual-homing 7-29  
dual-homing and multi-homing, VRs and 2-2  
duplex (setting) 2-20, 3-4  
dynamic option 11-15  
dynamic packet filtering. *see* FTP proxies  
dynamic paths  
  CSPF and 11-16  
  MPLS tunnels and 11-15  
dynamic-packet-filtering command 13-19

## E

E0. *see* E3  
E1 Concentrator 4-1  
E1 ID (option) 4-9  
E1. *see* E3  
E3 4-1–4-36  
  *see also* DS3  
  alarms 4-3  
    *see also* alarms  
  alarms and statistics, displaying 4-3  
  bandwidth 4-1, 5-1  
  channel configuration options 4-9  
    channel number 4-9  
    E1 ID 4-9  
    E1 number 4-9  
    HDLC ID 4-9  
    speed 4-9  
    time slot 4-9, 4-10

E3 (*continued*)  
  channel groups 4-10  
  channels  
    maximum number of 4-8  
    on port 3 4-8  
    viewing list of 4-10  
  Cisco HDLC and 4-10  
  Cisco interoperability 4-7, 4-31  
  commands  
    channel 4-9  
    controller 4-2  
    display 4-2  
    display tabular 4-3  
    shutdown 4-7  
  connectionless networks and 4-36  
  CRC-4 framing 4-4  
  DS3 and 4-1  
  E0s and 4-9  
    number of E0s per channel 4-8  
    performance of 4-9  
  E1 Concentrator units and 4-1  
  E1s and  
    accessing and modifying 4-6  
    bandwidth 4-8  
    fractional 4-8  
    settings 4-7  
    T1s and 4-6  
    viewing E1 information 4-5  
  events 4-3  
  frame engine E1 channel designations 4-8  
  Frame Relay and 4-2, 4-10–4-28  
    *see also* Frame Relay  
    overview 4-13  
    statistical bandwidth sharing 4-11  
  framing type and 4-5  
  FRoIP and 4-10, 4-36  
    *see also* FRoIP (Frame Relay over IP) 4-10  
  G.751 framing standard 4-4  
  interfaces  
    channelized, configuring 4-2–4-7  
    disabling 4-4, 4-7  
    serial. *see* serial interfaces  
    types, setting 4-16  
  Kentrox DSU mode 4-7, 4-31  
  loopbacks and, examples 4-5  
  national bit, ITU document G.704 4-7  
  performance monitoring 4-3  
    alarms 4-3  
  PPP and. *see* PPP (point-to-point protocol)  
  rate policing and 4-21  
  serial interfaces. *see* serial interfaces  
  settings  
    auto-detect 4-4  
    clock 4-32  
    framing 4-32

- E3 (*continued*)
  - settings
    - LCV 4-3
    - LES 4-3
    - loopback 4-32
    - LSES 4-3
    - SEFS 4-3
  - settings for configuration
    - clock 4-4
    - interface 4-4
    - international bit 4-6
    - loopback 4-5
    - national bit 4-4, 4-5, 4-6
    - test 4-5
  - testing, loopback setting and 4-5, 4-32
  - traffic and 4-5, 4-32
  - unchannelized. *see* unchannelized E3
- E3U. *see* unchannelized E3
- E-BGP connections, export policies and 7-10
- E-BGP multihop 8-8
  - using 8-24
- egbp-multihop option 8-8
  - using 8-24
- email protocols. *see* POP3 proxies, SMTP (simple mail transfer protocol)
- empty-tunnel-timeout setting 14-11
- enable (setting) 11-14
  - DS3 5-28, 5-32
  - E3 4-24, 4-29
  - IS-IS 9-5
  - OC-3 POS 6-44
  - PPPoATM 6-36
  - service-category setting and 6-30
- enable command 2-23
  - community strings and 2-24
- encapsulation 12-7
  - formats, unchannelized E3 and 4-32
  - types, supported 5-17
- encapsulation (setting) 2-20
  - abbreviation 4-33
  - options 6-27
- encapsulation command
  - channel-level link protocol and 4-23, 5-27
  - serial interfaces and 5-17
- encapsulation frame-relay command 4-13, 5-16
- encryption
  - ISAKMP/IKE and 12-17
  - keys, maximum length of 12-15
  - RSA 12-9, 12-19
- encryption (ISAKMP policy setting) 12-18
- encryption module (997-00001) 12-68
- encryption setting
  - PPTP and 13-57
- end address keyword 13-47
- ending address setting 13-46
- ending port setting 13-46
- end-user dialup connections, secure 14-2
- Entrust 12-9
- error checking
  - T1s 5-3
- error messages 5-50
  - see also* specific messages
- error thresholds
  - LMI 4-16, 5-19
- error types, E3. *see* alarms
- errored seconds
  - line 4-3, 5-10, 6-15
  - path 6-16
- errors, CRC and 6-6
- ES\_l performance counter setting 6-15
- ES\_p performance counter setting 6-16
- ES\_s performance counter setting 6-15
- ESF (extended superframe format) 5-2, 5-3
  - DS3 and 5-9
- ESP. *see* IPSec
- esp-3des keyword 12-22
- esp3-md5-hmac keyword 12-22
- esp3-sha-hmac keyword 12-22
- esp-des keyword 12-22
- esp-des-rfc1829 mode 12-22
- esp-md5-hmac keyword 12-22
- esp-sha-hmac keyword 12-22
- Ethernet
  - MPLS and 11-1
- ethernet (command), abbreviation 2-19
- Ethernet blades
  - as logical interfaces 3-7
  - cabling 3-1
  - commands
    - show blade 3-2
  - configuring 3-2–3-6
  - Ethernet ports. *see* Ethernet ports
  - number of physical ports 3-3
  - port-level tasks 3-5
  - settings 3-4
    - autoneg 3-4
    - duplex 3-4
    - speed 3-4
    - status 3-4
  - viewing 3-3
  - VIs and 3-5
  - VLAN connections 3-7
  - VLANs and 3-1, 3-2
- Ethernet ports
  - see also* Ethernet blades
  - autonegotiation 3-4
  - commands, obtaining information for 2-19
  - configuring 2-19–2-20
  - duplex setting 3-4
  - IP address 1-5

### Ethernet ports (*continued*)

- line speed 3-4
- number of, in network connectivity 3-3
- operating status 3-4
- settings
  - autonegotiation 2-20
  - encapsulation 2-20
  - line speed 2-20
  - for status monitoring and reporting 2-20
  - transmission directions 2-20
  - using default values 2-20
- specifying 1-5, 1-8
- VIs carrying VLAN traffic and 3-10

### European DS3. *see* E3

- event-log area adjacency command 9-27
- event-log area command 9-27
- event-log area lsp command 9-27
- event-log area spf command 9-27
- event-log level command 9-27
- events

- DS3 5-10
- E3 4-3
- logging
  - in BGP-4 8-32
  - in PPP sessions 4-30, 5-33

### event-window-size setting 5-45

### excess burst size (Be). *see* Be (excess burst size) setting

### expire-timer setting 12-14

### explicit label-switched path 11-3

### explicit path\_name option 11-15

### explicit paths

- creating 11-7
- CSPF and 11-9
- defining 11-27
- example 11-29
- inserting IP addresses into 11-8
- loose keyword 11-29
- MPLS tunnels and 11-15
- showing IP addresses in 11-8
- specifying next IP address for 11-9

### explicit-path setting 11-7

- loose and strict keywords 11-7, 11-29

### export policies 7-3–7-10

- ACLs and 7-4
  - reusing ACLs 13-8
- BGP community attribute
  - IETF RFC 1997 7-12
  - IETF RFC 1998 7-12
  - no-advertise value 7-12
  - no-export value 7-12
  - proprietary values 7-12
- BGP community attribute and 8-25
- BGP neighbor router 7-11
- BGP-4 and 8-3
- BGP-AS 7-11

### export policies (*continued*)

- changing 7-15
  - creating 7-10–7-16
    - example 7-15
  - example 7-14
  - IS-IS metric types 7-14
  - metric value for exported route 7-11
  - multi-exit discriminator (MED), using 7-16, 8-18
  - OSPF and 10-7, 10-13
    - exporting routes from OSPF backbone 7-13
    - exporting routes from OSPF external type 1 and type 2 7-13
    - exporting routes from OSPF stub area 7-13
  - external type 1 routes 7-13
  - external type 2 routes 7-13
  - route-type setting for 7-13
  - preventing exportation of internal BGP routes 7-16
  - protocol specification 7-11
  - purposes 7-3
  - required values 7-16
  - RIP prefix for export 7-11
  - route filtering and 7-10
  - route-type field, for IS-IS 7-13
  - routing directives and 7-2
  - routing types 7-15
  - settings 7-11
    - ACL 7-11
    - action 7-11
    - BGP-community 7-12
    - ext-rte-tag 7-11
    - level 7-14
    - metric 7-11
    - met-type 7-14
    - neighbor 7-11
    - peer-AS 7-11
    - protocol 7-11
    - RIP-IP 7-11
    - route-type 7-13
  - supported communities 8-25, 8-26
  - typical uses 7-10
  - use of ACLs in 7-11
  - using in IS-IS 9-6
  - VRs and 8-13
- ### export-policy option 8-8
- ### export-policy setting 9-6
- ### exterior routing protocols 8-1
- ### ext-rte-tag setting 7-11

## F

- facility data link 5-3
- failover capabilities 7-34
- failures, OC-3c 6-15
- FC\_1 performance counter setting 6-15
- FC\_p performance counter setting 6-16

- FCS (frame check sequence), Cisco routers and 6-39
- feature setting 13-25
  - recommendations 13-25
- FECN (forward explicit congestion notification) 4-11, 5-14
  - dropped frames and 4-12, 5-15
- fiber optic cables 6-7
- files, configuration
  - names of 1-8
  - naming 1-6
- filter # (setting) 13-9
- FilterID setting 7-27
- finger port 13-7
- firewall setting 13-6, 13-9
- firewalls 13-1–13-58
  - access tables 13-12
    - action setting 13-13
    - control blades and 13-12
    - creating 13-12
    - destination address 13-13
    - in SMTP proxies 13-28
    - in SMTP proxy 13-33
    - number of entries in 13-14
    - policy setting 13-13
    - priority number (ID) 13-15
    - proxy servers and 13-12
    - source address 13-13
    - TCP port value 13-13
    - viewing individual records 13-14
  - ACLs and 7-4, 13-4
  - IPSX switches and 1-12
  - packet filters. *see* packet filters
  - proxy, routing transmissions to 13-9
  - routing decisions 13-4, 13-44
  - viewing status of 1-18
- Firewalls and Internet Security*, by Cheswick & Bellovin 13-4
- flag setting 12-25, 12-36
  - using 12-26
- flash memory
  - booting from 1-5
  - saving image software into 1-6, 1-8, 1-9
  - using 1-6, 1-8, 1-9
- flow classification 11-23
- flow-control setting 14-12
- /FLSH/ ipnos entry 1-5
- FR. *see* Frame Relay
- fractional E1 4-8
- FRADs (Frame Relay access devices) 4-11, 5-14, 5-41
  - interface types and 4-16, 5-19
- Frame Relay
  - Bc (committed burst size) 5-23
  - BECN 4-11, 5-14
    - dropped frames and 4-12, 5-15
  - CIR (committed information rate) 4-11, 5-14
  - Cisco, settings 4-15, 5-18
- Frame Relay (*continued*)
  - commands
    - encapsulation frame-relay 4-13, 5-16
    - frame-relay route 4-13, 5-16
    - interface serial 4-13, 5-16
    - interface-dlci 4-13, 5-16
    - interface-type 4-13, 5-16
    - obtaining help for 4-25, 5-29
    - rate-police 4-13, 5-16
  - configuring 5-14–5-21
    - DLCIs and 4-21, 4-27, 5-24, 5-31
  - connections, testing 4-13, 5-16
  - connectivity over DS3. *see* DS3
  - connectivity over E3. *see* E3
  - considerations when configuring 4-27, 5-31
  - data sequencing 5-41
  - devices, access. *see* FRADs (Frame Relay access devices)
  - DLCIs 4-11, 5-14
    - assigning to a subinterface 4-22, 5-25
    - creating 5-45, 5-46
    - defining 4-13, 5-16
    - example 4-13, 5-16
    - identifying 4-13, 5-16
    - importance of 4-18, 5-21
    - number of according to LMI type 4-22, 5-25
  - DS3 and. *see* DS3
  - examples
    - DS3 5-29
    - E3 4-26
  - FECN 4-11, 5-14
    - dropped frames and 4-12, 5-15
  - FRADs. *see* FRADs (Frame Relay access devices)
  - frame counts, discarded 4-19
  - HDLC channels and 4-13, 5-16
  - indicators of dropped frames 4-12, 5-15
  - over IP. *see* FRoIP (Frame Relay over IP)
  - IPSec and. *see* IPSec
  - keepalive interval 4-12, 5-15
  - keepalive setting
    - using 4-17, 5-20
  - line management formats 4-17, 5-20
  - LMI. *see* LMI (local management interface)
  - NNIs 4-11, 5-14
  - on DS3 blades 5-14
  - on OC-3 POS blades 6-37
  - on unchannelized DS3 ports 5-36–5-38
    - commands for 5-36
  - on unchannelized E3 ports 4-33–4-35
    - commands for 4-33
  - over POS. *see* OC-3 POS (packet over SONET)
  - point-to-point links 4-21, 5-24
  - PPP and. *see* PPP (point-to-point protocol)
  - protocol-specific bandwidth allocations 4-21, 5-24
  - provisioning 5-1–5-51

### Frame Relay (*continued*)

- PVCs 4-10, 4-11, 5-14
  - see also* PVCs (permanent virtual circuits)
  - DLCIs and 4-13, 5-16
  - on unchannelized DS3s 5-38
- rate policing. *see* rate policing
- settings
  - Bc, Be, and CIR 4-13, 5-16
  - frame-relay 4-15, 5-18
- statistical multiplexing 4-11
- status inquiry sequence 4-16, 5-19
- subinterfaces. *see* subinterfaces
- terminology 5-14
- testing, recommendations 4-17, 5-20
- traffic, interface type and 4-15, 5-18
- unchannelized DS3. *see* unchannelized DS3
- unchannelized E3. *see* unchannelized E3
- UNI 4-18, 5-21
- UNIs 4-11, 5-14
- VIs and
  - bandwidth 4-13, 5-16

Frame Relay over IP (FRoIP). *see* FRoIP (Frame Relay over IP)

FRAME-RELAY CLI command level 4-14

FRAME-RELAY command level 5-17

frame-relay route command 4-13, 5-16

frame-relay setting 4-15, 5-18

### frames

- allowing or disallowing 13-25
- discarded counts 4-19
- dropped, indicators of 4-12, 5-15

framing (setting) 4-7, 4-32, 6-5

- OC-3 POS framing types and 6-40

### framing standards

- c-bit 5-7
  - c-bit path code violations 5-10
  - c-bit path errored seconds 5-10
  - c-bit path severely errored seconds 5-10
- data 5-3
- G.751 4-4, 4-32
- M23 5-7
  - p-bit path code violations 5-10
  - p-bit path errored seconds 5-10
  - p-bit path severely errored seconds 5-10

### framing types

- E3 and 4-5
- OC-3 POS and 6-39

### FRoIP (Frame Relay over IP) 5-40–5-51

- access blade types 5-50
- buffered packet sequence length 5-45
- configuring 5-42–5-49
  - example 5-44, 5-47
- connectionless IP networks and 4-36, 5-40
- DS3 and 5-41
- E3 and 4-10, 5-41

### FRoIP (Frame Relay over IP) (*continued*)

#### FRoIPSec 5-51

*see also* IPSec

- identification of 5-41
- IPNOS version 5-41
- local VIs and 5-41, 5-42
- settings 5-43
  - admin-status 5-45
  - default-window-size 5-43
  - default-window-timeout 5-43
  - DLCI (setting) 5-45
  - for DLCIs 5-47
  - event-window-size 5-45
  - frame sequencing 5-41
  - keep-alive-period 5-45
  - local VI 5-43
  - max-transport 5-43
  - permit-bad-event 5-45
  - route 5-49, 5-50
  - transport (setting) 5-43
  - window sizes 5-43, 5-45
  - window-size 5-45
  - window-timeout 5-45
- subscriber VRs and 5-41
- transports 5-42, 5-49
  - creating 5-43
  - DLCIs and 5-45
  - enabling or disabling configuration 5-45
  - number of 5-43
  - settings 5-45
  - window sizes 5-43, 5-45
- tunnels 5-49
- unchannelized E3 and 5-41

#### FRoIPSec (Frame Relay over IPSec) 5-51

### FTP (file transfer protocol)

- command channel 13-8
  - data channel 13-8
  - port 13-7
  - servers, enabling user logins 13-21
- ### FTP proxies
- actions, enabling 13-19
  - child-limit setting 13-16
  - creating 13-16
    - viewing configuration 13-16
  - dynamic packet filtering 13-19, 13-22
  - dynamic-packet-filtering command 13-19
  - enabling proxy logging 13-22
  - func command 13-19
  - functions
    - default state 13-21
    - enabling or disabling 13-20–13-22
  - get command 13-21
  - handoff command 13-19
  - listen command 13-16
  - logged command 13-19

- FTP proxies (*continued*)
    - policy setting 13-16
      - cross-referencing access tables 13-17
    - put command 13-21
    - servers 13-11
    - syslogD and 13-22
    - timeout setting 13-19
  - func command 13-19
    - FTP functions and 13-20–13-22
    - HTTP proxies 13-24
    - no func all
      - caution 13-21
    - pwd option 13-21
    - recommendations 13-25
    - user option 13-21
- G**
- G.704 (ITU document) 4-7
  - G.751 framing standard 4-4, 4-32
  - GALs (general access lists). *see* ACLs (access control lists)
  - gateway command 1-5
  - gateway setting 1-8
  - gateways, SA, lifetime values 12-20
  - GenAcIID setting 7-27
  - general access lists (GALs). *see* ACLs (access control lists)
  - get command 13-21
  - global commands 1-13
  - group (ISAKMP policy setting) 12-18
- H**
- handoff command 13-19
    - HTTP proxies 13-24
  - hard rekey 12-3
  - hard-kilobytes setting 12-3, 12-20
    - Cisco routers and 12-20
  - hard-seconds setting 12-3, 12-20
  - hash (ISAKMP policy setting) 12-18
  - HDLC (high-level data link control) 5-3
    - channels, PPP over. *see* PPP (point-to-point protocol)
    - DS0s and 5-12
    - DS0s in 5-11
    - DS3 channels and 5-3
      - on DS3s 5-11–5-13
        - configuration 5-13
        - serial interfaces and 5-13
      - on unchannelized DS3 ports 5-39
      - on unchannelized E3 ports 4-36
      - OSI layer 2 protocol 4-36, 5-39
      - over SONET/SDH 6-46
      - VCI and 6-2
    - HDLC ID (option) 4-9, 5-12
    - header setting 13-25
      - recommendations 13-25
    - Hello (setting) 14-11
      - Hello PDUs 9-16
        - authenticating 9-10
        - intervals between 9-11
        - passive setting and 9-9
      - Hello query packets 14-11
      - hello-interval setting 9-12, 10-10
      - hello-multiplier setting 9-12
      - help (command) 1-5, 1-14
        - boot configuration 1-3
      - help for commands and settings
        - capital letters in 1-14
        - searching 1-15
        - understanding how to use 1-14
      - hexadecimal keys vs. ASCII 12-34
      - HMAC algorithm 12-7
      - home-AS setting 7-8
      - hopcount option (traceroute command) 2-17
      - host channels
        - serial interfaces and 4-14, 5-16
      - host command 1-5
        - SNMP 2-23
      - host names
        - L2TP and 14-3
      - host setting 1-8
      - hosts
        - for IPSX software 1-2
        - IS-IS 9-15
        - SNMP
          - community strings and 2-25
          - enabling 2-24
        - TFTP. *see* TFTP
      - hot spots
        - avoiding 11-22
        - RSVP and 11-23
      - HP OpenView, SNMP port setting and 2-23
      - HP-UX 1-2
      - HTTP port 13-7
      - HTTP proxies
        - address translation 13-27
        - child-limit command 13-23
        - command examples 13-26
        - creating 13-22
          - examples 13-23
        - enabling features 13-25
        - feature setting 13-25
        - handoff command 13-24
        - header types 13-25
        - host and domain names 13-24
        - listen command 13-23
        - no feature all command 13-25
        - no func all command 13-25
        - no header all command 13-25
        - no logged all command 13-25
        - ourname command 13-24
        - policy setting 13-23

- HTTP proxies (*continued*)
  - purpose 13-22
  - servers 13-11
  - syslogD and 13-24
  - timeout limit 13-24
  - Web extensions and languages
    - allowing or disallowing 13-25
- I
- IANA (Internet Assigned Numbers Authority) 13-6
- I-BGP. *see* BGP-4 routing
- IBM AIX 1-2
- ICMP (Internet control message protocol)
  - packets, timeout duration 2-16
  - requests, ping command and 2-16
- ICR (initial cell rate) setting 6-26
  - traffic descriptors and 6-23
- identity-PFS (crypto map flag value) 12-27
- idle-timeout setting
  - PPTP and 13-57
- IEEE 802.1Q VLAN standard 3-1
- IETF RFC 2661, L2TP and 14-7
- IETF RFC 1195 9-1
- IETF RFC 1245 10-1
- IETF RFC 1246 10-1
- IETF RFC 1247 10-1
- IETF RFC 1541, DHCP and 13-52
- IETF RFC 1771 8-1
- IETF RFC 1793 10-1
- IETF RFC 1997 7-12
- IETF RFC 1998 7-12, 8-26
- IETF RFC 2205 11-1
- IETF RFC 2209 11-1
- IETF RFC 2430 11-1
- IETF RFC 2439 8-1
- IETF RFC 2474 7-17
- IETF RFC 2547 11-1
- IETF RFC 2702 11-1
- IETF RFC 2763 9-1
- IETF RFC 2917 11-1
- IETF RFC 3031 11-1
- IETF RFC 3032 11-1
- IETF RFC 3034 11-1
- IETF RFC 3035 11-1
- IETF RFCs, OSPF and 10-1
- IETF routing protocol RFCs 7-2
- IF-name setting 6-9
- ignore-CR-payload flag 12-16
- IGPs (interior gateway protocols)
  - autonomous systems and 7-35
  - export policies and 7-11, 7-16
  - for the control network 1-25
  - IS-IS. *see* IS-IS routing
  - ISP networks and 7-31
- IGPs (interior gateway protocols) (*continued*)
  - MPLS and 11-21
  - OSPF. *see* OSPF (open shortest path first)
  - subscriber networks and 7-31
- IGRP (Cisco routing protocol) 10-6
- IIH (IS-IS Hello) PDUs 9-12, 9-16
- IKE 12-16
  - see also* ISAKMP
  - characteristics 12-17
  - hardware encryption in 12-17
  - SAs 12-16
    - supports multiple policies during negotiation 12-17
- IKE key setting 12-25
- IKE-key setting 12-36
- IKE-policy setting 12-25, 12-36
- ILMI version setting 6-10
- ILMIs (integrated local management interfaces). *see* ATM (asynchronous transfer mode)
- ILMI-VCI setting 6-10
  - importance of using default values 6-11, 6-13
- ILMI-VPI setting 6-10
  - importance of using default values 6-11, 6-13
- image file configuration paths, changing 1-4
- images, boot
  - directories for 1-8
- import policies 7-3–7-10
  - ACLs and 7-4
    - reusing ACLs 13-8
  - BGP community attribute and 8-25
  - BGP-4 neighbors and 8-9
  - changing 7-9
  - creating 7-8–7-10, 8-25
    - commands for 7-9
  - example 7-9
  - not supported by IGPs in IPNOS 7-10
  - purposes 7-3
  - routing directives and 7-2
  - settings 7-8
    - ACL 7-8
    - action 7-8
    - BGP-community 7-8
    - home-AS 7-8
    - origin 7-8
    - peer-AS 7-8
    - preference 7-8
  - supported communities 8-26
  - use of ACLs in 7-8
  - values, required 7-10
  - viewing 7-9
  - VRs and 8-13
- inbound AH key setting 12-30
- inbound AH SPI setting 12-30
- inbound ESP authenticator setting 12-31
- inbound ESP SPI setting 12-31
- inbound setting 13-9

- inbound/outbound setting 7-27
- information rate 4-11, 5-14
- information rate, committed. *see* subinterfaces
- InGage Customer Network Management (CNM) system,
  - documentation for xxiii
- inhibition registers. *see* OC-3c
- init values, adjacencies and 9-19
- initial configuration 1-24
  - see also* boot configuration
  - control VPNs and 1-24
- initiators and responders. *see* IPSec
- init-vector setting 12-23
- interface (setting) 4-4, 4-32, 5-7
- interface atm command 6-4
- interface command, abbreviation 2-19
- interface serial command 4-13, 5-16, 5-35
  - unchannelized DS3 and 5-37
  - unchannelized E3 and 4-34
- interface-dlci command 4-13, 5-16
- interface-DLCI setting 4-20, 5-23
- interfaces
  - DCE and DTE. *see* LMI (local management interface)
  - disabling, shutdown command and 4-32
  - serial. *see* serial interfaces
  - timers, OSPF 10-9
  - types of 2-11
    - Frame Relay and 4-15, 5-18
    - setting 4-16, 5-19
  - UNI 4-18, 5-21
- interface-type command 4-13, 5-16
- international bit setting 4-6
- Internet Assigned Numbers Authority (IANA) 13-6
- Internet protocol security. *see* IPSec
- Internet relay chat port 13-7
- Internet security association and key management protocol (ISAKMP). *see* ISAKMP
- intf-type command 4-16, 5-19
- InVision SMS 1-24
  - documentation for xxiii
  - firewall access tables and 13-12
  - IPNOS communications 2-22
  - synchronizing with CLI 1-7
  - tunnel interface terminology 12-40
- IOS mode 1 4-7, 4-31
- IP
  - area addresses and 9-5
  - data sequencing 5-41
- IP address pools
  - NAT and 13-46
  - use with L2TP 14-2
- IP addresses
  - 0.0.0.0, ACLs and 13-5
  - 165.165.100.100 and 165.165.100.99 2-21
  - advertising as IS-IS internal routes 9-9
  - control VR 2-21
- IP addresses (*continued*)
  - DHCP servers 13-53
  - explicit paths and 11-9
    - inserting into 11-8
    - listing 11-8
  - in ACLs 13-5
  - local 1-5, 1-8
  - loopback interfaces and 2-8
  - MPLS tunnel VIs and 11-9
  - NMSs 2-23
  - OC-3c interfaces 6-10
  - TFTP host 1-5, 1-8
  - VI 1 and 2-4
  - VIs and 2-6
  - VRs and 2-3
- IP forwarding, configuring 7-1–7-38
- ip local pool setting 13-56, 14-3
- ip nat list setting 13-45
  - example 13-48
  - list ID keyword 13-48
  - pool ID keyword 13-48
  - VI ID keyword 13-48
- ip nat pool setting 13-45
  - example 13-46
  - poolID index number 13-46
  - starting and ending addresses 13-46
  - TCP/UDP port ranges 13-46
- IP networking services, viewing status of 1-18
- ip ospf area command 10-4
- ip ospf authentication-key setting 10-12
- ip ospf message-digest key setting 10-12
- ip ospf priority setting 10-11
- ip route command
  - creating default routes 7-29
  - metric value 7-30
  - static routes and 7-29
    - to add static routes 12-54–12-57
- IP source routing, rsh and 13-39
- IP spoofing, rsh and 13-39
- IP subnets, VLANs and 3-2
- IP-Address setting 2-23
- IP-local-pool-name setting, L2TP PPP 14-10
- IPoATM (IP over ATM) 6-26
  - enabling 6-25, 6-34
  - packet encapsulation types and 6-26
- IP-pool setting 13-57
- IPSec
  - advantages 12-2
  - AH
    - AH transport 12-7
    - characteristics 12-7
    - MD5 or SHA-1 12-7
  - authentication. *see* authentication algorithms
  - BOOTP flag and 12-28
  - certificate configuration level 12-11

### IPSec (*continued*)

- connected-to command, using 12-40
- connections
  - verifying 12-47
  - verifying with ping 12-47
  - verifying with traceroute 12-47
- crypto isakmp parameter command 12-12
  - required for IPSec operation 12-12
- crypto map flags. *see* crypto map flags
- crypto map IPSec/ISAKMP configuration level 12-11
- crypto map. *see* crypto map
- crypto transform-set command
  - used in deployment 12-9
- crypto transform-set configuration level 12-11
- default ISAKMP settings (ISAKMP parameter) 12-11
- default settings
  - using while creating connections 12-52
- DES and 12-6
- Diffie-Hellman
  - explained 12-8
  - groups 1, 2, and 5 12-18
  - in IPSX CLI example 12-52
- disadvantages 12-3
- encapsulation 12-7
- ESP transport mode
  - advantages 12-6
- ESP tunnel mode 12-7
  - advantages 12-6
  - described 12-7
- failover mechanism
  - characteristics 12-57
  - designated tunnel VI 12-58
  - dual-homed subscriber VRs 12-58
- IKE. *see* IKE
- initiator and responder 12-2, 12-5, 12-9
- interoperability with Cisco 12-8, 12-20
- interoperability with Nortel Contivity 12-20
- IPSec-dialup crypto map. *see* IPSec-dialup crypto map
- IPSec-manual crypto map. *see* IPSec-manual crypto map
- ISAKMP lifetime. *see* ISAKMP lifetime
- ISAKMP parameter. *see* ISAKMP parameter
- ISAKMP. *see* ISAKMP
- L2TP and Windows 2000 and 14-16
- manual key formats for Redback, Cisco, and CoSine 12-34
- manual key settings for ISAKMP 12-11
- mixed mode 12-68
- over a sample Frame Relay network 12-48
- PFS 12-28
  - dependencies 12-27
  - for ISAKMP only 12-27
- proposals 12-21
  - ISAKMP policy 12-9
  - ISAKMP policy database 12-21
  - software-based modes for 12-22

### IPSec (*continued*)

- proposals 12-21
  - transform-set database 12-21
  - transform-set database keywords 12-22
  - transform-set database recommendations 12-22
- public key 12-9
- recommendations 12-67
- rekey settings
  - see also* ISAKMP lifetime
  - advantages 12-3
  - soft and hard 12-3
- remote clients and 12-26
- SAs
  - 0.0.0.0 routes 12-47
  - creating 12-9
  - importance of 12-5
- security parameter index (SPI) 12-7, 12-16
- session keys 12-2, 12-8
- SHA-1 algorithm 12-7
- static routing 12-53
  - default routes for ISP VRs 12-53
  - default routes for subscriber VRs 12-53
  - entering default routes for ISP VR 12-55–12-57
  - ISP VR requirements 12-53
  - local tunnel VI as the next hop 12-53
  - routing comments 12-53
  - static routes for ISP VRs 12-53
  - static routes for subscriber VRs 12-53
  - subscriber VR features 12-54–12-55
- symmetrical encryption 12-8
- transform key sizes 12-33
- transform-set database
  - changing transform-set settings 12-23
  - init-vector setting 12-23
  - selecting tunnel or transport mode with mode setting 12-23
- transport mode 12-29
  - L2TP and 14-2
- triple-DES 12-2, 12-6, 12-18, 12-28
  - in crypto transform-sets 12-22
  - interoperability and 12-8
  - supported in IPSX ISAKMP policies 12-18
- tunnel mode
  - headers and 12-2
- tunnel VIs
  - characteristics 12-45
  - run on same subnet 12-45
- tunnels
  - connected-to command and 12-40
  - ensuring stability 12-67
  - how they operate 12-2
  - termination points 12-39
  - verifying with traceroute command 12-47
- VPNs 12-2
  - IPSX switches and 1-12

- IPSec transform set 12-37
- IPSec-dialup crypto map 12-35
  - see also* IPSec
  - aggressive-mode 12-36
  - certificate setup in CLI 12-38
  - command examples 12-38
  - domain name qualifier 12-37
  - formatting and arguments for distinguished name 12-37
  - host-to-host 12-36
  - IKE-key field for pre-shared key 12-36
  - IKE-policy command 12-36
  - local-ISAKMP-identity command for digital certificate 12-37
  - main-mode 12-36
  - pre-shared keys and 12-38
  - settings
    - flag 12-36
    - IKE-key 12-36
    - IKE-policy 12-36
    - local-ISAKMP-identity 12-37
    - PFS-group 12-37
    - security-association 12-37
    - transform-set 12-37
- IPSec-manual crypto map
  - transform-set key sizes 12-33
- IPSec-manual crypto map
  - see also* IPSec
  - AH and ESP and 12-34
  - creating 12-29
  - creating session keys 12-31
  - crypto map example 12-33
  - disadvantages 12-29
  - 8-byte key length 12-29
  - inbound and outbound ESP cipher 12-31
  - map names
    - changing 12-30
  - match address command for using ACLs 12-29
  - security parameter index (SPI) 12-33
  - security parameter index values 12-30–12-31
  - settings
    - match address 12-30
    - name 12-30
    - session-key 12-30
    - transform-set 12-30
  - specifying ACL 12-30
  - transform key sizes 12-33
  - use of MD5 or SHA-1 12-32
  - using ACLs 12-29
  - using symmetrical keys 12-32
- IPSX 9000
  - boot configuration and 1-1
  - documentation for xxii
  - network interfaces and 6-8
  - timeout limits 1-6
- IPSX software
  - see also* boot configuration
  - installing new version 1-2
- IPSX switches 1-12
  - ATM configuration on 6-2
  - ATM networking and 6-18
  - bandwidth 5-3
  - configuring
    - saving configuration 1-8
    - viewing configuration status 1-18
  - locating installed DS3 blades 5-4
  - methods for configuring 1-24
  - restarting 1-9
- IPSX, VLANs and 3-2
- IPX/SPX 13-54
- IRE dial-up client 12-11
  - digital signatures and certificates or pre-shared keys 12-35
  - IPSec-dialup crypto map and 12-35
  - operating systems 12-35
  - operation, SA-per-net flag and 12-27
- ISAKMP 12-4–12-5, 12-16
  - authentication algorithm 12-18
  - DES and 12-18
  - encryption and 12-17
  - ISAKMP SA 12-16
  - main mode 12-7, 12-8
  - manual key settings 12-11
  - multiple ISAKMP policies per VR 12-16
  - Oakley extension 12-8
  - phase I 12-4, 12-7
    - interoperability and 12-8
    - session key 12-5
  - phase II 12-4, 12-8
    - session key 12-3
  - policies, creating 12-17
  - SAs 12-8
  - setting aggressive-mode 12-28
  - settings 12-11
- ISAKMP lifetime 12-19
  - hard-kilobytes setting 12-3, 12-20
    - Cisco routers and 12-20
  - hard-seconds setting 12-3, 12-20
  - hard-seconds setting for phase I rekeys 12-19
  - lifetimes determining rekey intervals 12-19
- ISAKMP parameter
  - anti-clogging 12-14, 12-15
  - as a configuration level 12-11
  - defaults, retention of 12-13
  - flags 12-15
    - for older IETF RFCs 12-16
    - for packet payload padding 12-16
    - for using older ISAKMP features 12-16
    - ignore-CR-payload 12-16
    - use-zero-SPI 12-16

### ISAKMP parameter (*continued*)

- ISAKMP transactions and policies and 12-13
- local-secret-size setting 12-15
- maximum length of an encryption key 12-15
- maximum time allowed for negotiation 12-14
- number of retries 12-14
- permissible number of SAs 12-15
- secret-recreate setting 12-14
- setting at the VR level 12-12
- settings 12-14
  - address 12-14
  - expire-timer 12-14
  - max-key-len 12-15
  - max-retry-timer 12-14
  - max-SA-count 12-15
  - port 12-14
  - retry-limit 12-14
  - retry-timer-sec 12-14
  - retry-timer-usec 12-14
  - secret-recreate 12-14
  - SPI-size 12-15
  - token-hash-type 12-15
  - VPN, VR, and NAME 12-14
- to enable ISAKMP 12-9
- UDP port monitoring 12-14

### ISAKMP policy (configuration level) 12-11

### IS-IS

- export policies route-type field and 7-13
- in service provider networks 7-35
- metric types for export policies 7-14
- policy for exporting Level 1 routes 7-13
- policy for exporting Level 2 routes 7-13
- subscriber VRs and 7-35

### isis circuit detail command 9-10

### IS-IS routing 9-1–9-27

- area addresses and 9-5
- area borders 9-15
- authentication 9-10–9-11
  - area-password 9-10
  - domain-password 9-10
  - isis circuit detail (command) 9-10
  - isis-password 9-10
  - passwords 9-10
- characteristics of 9-15
- circuits, viewing 9-21
- circuit-type command 9-16
- commands 9-2
  - event-log area 9-27
  - event-log level 9-27
  - router isis 9-3
  - show 9-19–9-26
- configuring
  - basic configuration 9-3
  - key elements 9-4
  - notes 9-15–9-16

### IS-IS routing (*continued*)

- configuring
  - viewing configuration 9-3, 9-6, 9-21
- database, viewing 9-22
- designated routers 9-9, 9-11, 9-15
  - backup 9-15
- enabling 9-5, 9-9
- end systems (hosts) 9-15
- event logging, enabling 9-26
- export policies and, using 9-6
- hierarchy 9-17–9-18
- hold-time 9-12
- IIH (IS-IS Hello) 9-12
- interfaces 9-8–9-10
  - circuit-type 9-8
  - passive (setting) 9-9
  - priority 9-9
  - router isis 9-9
- internal networks and 9-1
- ISP VRs and 9-15
- Level 2 router 9-15
- metrics 9-14–9-15
  - metrics 9-14
  - metric-style 9-14
- monitoring and troubleshooting 9-3, 9-19–9-26
- MPLS and 11-3
- non-IP applications 9-15
- packet types 9-16
- protocol data units (PDUs)
  - authenticating 9-10
  - control PDU counters 9-22
  - CSNP 9-16
  - Hello 9-16
  - intervals between sending CSNPs 9-11, 9-13
  - intervals between sending hello PDUs 9-11
  - link-state 9-13, 9-16
  - partial sequence number 9-13, 9-16
- route summarization 9-7
- router ID to system-ID 9-8
- routers 9-5–9-8
  - area-address 9-5
  - default-info-originate 9-5
  - enable 9-5
  - export-policy 9-6
  - level-2-to-1-leaking 9-6
  - show config 9-6
  - spf-interval 9-7
  - summary-address 9-7
  - system-id 9-7
  - system-type 9-8
- settings
  - area-address 9-4
  - circuit-type 9-4
  - metric 9-4
  - net 9-4

IS-IS routing (*continued*)

- settings
    - system-id 9-4
    - system-type 9-4
    - viewing 9-20
  - shortest path first 9-1
  - statistics, viewing 9-26
  - subscriber VRs and 9-15
  - system ID 9-6
  - timers 9-11–9-14
    - Cisco routers and 9-11
    - csnp-interval 9-11, 9-13
    - dr-hello-interval 9-11
    - hello-interval 9-12
    - hello-multiplier 9-12
    - hold time 9-12
    - intervals between retransmissions 9-13, 9-14
    - isp-interval 9-13
    - Juniper routers and 9-11
    - psnp-interval 9-13
    - retransmit-interval 9-13
    - retransmit-throttle 9-14
  - topology in ISP core 9-12
  - viewing configuration and statistics 9-3
- isis-password setting 9-10
- ISO 9-15
- ISO standard 10589 9-1
- ISP networks, IGPS and 7-31
- ISP routers, control VRs and 1-23
- ISP VRs 1-22, 1-23
  - AS confederations and 8-22
  - BGP-4 and 1-23, 8-3
  - deployment characteristics 2-2
  - example 7-33
  - filtering in 2-2
  - IS-IS and 9-15
  - Level-1 and Level-2 routers and 9-16
  - route filtering 10-13
  - routing protocols in 2-2
  - static routes and 12-64
  - subscriber VRs and 1-22
- isp-interval setting 9-13
- ITU document G.704, E3s and 4-7

**J**

- J0 setting 6-6
- Japanese ATM networks, J0 setting and 6-6
- Java, allowing or disallowing 13-25
- Javascript, allowing or disallowing 13-25
- Juniper
  - diff-serve and 7-17
  - IS-IS and, timer commands 9-11

**K**

- Kanji, allowing or disallowing 13-25
- keepalive interval 4-12, 5-15
- keepalive setting, L2TP PPP 14-10
- keepalive status inquiry polling interval 4-16, 5-19
- keep-alive-period setting 5-45
- keep-image command 1-9
- Kentrox DSU mode
  - Cisco and 4-7, 4-31
- kerberos port 13-7
- key point, explanation of xxi
- keys, manual, formats 12-34
- keywords
  - no 1-17
    - proper use of 1-17
  - viewing 1-14

**L**

- L2TP (layer 2 transfer protocol) 14-1–14-34
  - see also* PPTP (point-to-point tunneling protocol)
  - address pool limit 14-3
  - characteristics 14-2
  - configuration at VR level 14-4–14-8
  - connections, creating 14-13–14-34
  - hardware, substituting IPNOS features for 14-1
  - ip local pool setting 14-3
    - purpose of 14-3
  - IPNOS LNS support 14-1
  - ISP authentication password 14-2
  - L2TP access concentrator (LAC) 14-1
  - LAC and LNS in same VI 14-2
  - lns admin-status enable command 14-13
  - multi-hop 14-7
- PPP
  - configuring 14-9
    - flow control, enabling or disabling 14-12
    - packet buffer size 14-12
    - packet sequencing 14-12
    - settings 14-10
    - username database 14-4
  - primary use 14-2
  - processor engine requirement 14-2
  - RADIUS support 14-2
  - RFC 2661 compliance 14-7
  - service VI 14-22
  - service-VI setting 14-8
  - session and tunnel configuration
    - max-sessions-per-tunnel setting 14-8
    - max-tunnel setting 14-8
    - service-VI setting 14-8
  - session submenu 14-8
    - flow-control setting 14-12
    - packet-sequencing setting 14-12
    - receive-window-size setting 14-12

- L2TP (layer 2 transfer protocol) (*continued*)
  - session submenu 14-8
    - settings 14-12
    - transmit-queue-size setting 14-12
  - sessions 14-3
    - settings 14-10
    - tearing down 14-15
  - settings
    - L2TP 14-7
    - lac admin-status drain 14-7
    - lac admin-status enable 14-7
    - lns admin-status drain 14-7
    - lns admin-status enable 14-7
    - PPP 14-7
    - tunnel 14-7
    - tunnel-switch 14-7
  - testing 14-13
  - tunnel submenu 14-8
    - empty-tunnel-timeout setting 14-11
    - Hello query 14-11
    - max-retransmission setting 14-11
    - retransmission-timeout setting 14-11
    - settings 14-11
    - tunnel authentication 14-11
    - tunnel receive-window-size setting 14-11
  - tunnel switching 14-30–14-34
    - between LNS and LAC 14-32
    - configuring 14-31
    - enabling 14-31
    - modes 14-32
  - tunnels
    - ID numbers 14-7
    - inspecting 14-14
    - requirements 14-2
    - tearing down 14-15
  - user authentication, RADIUS and PPP and 14-3
  - VIs and 14-8
  - Windows 2000 and 14-2, 14-15–14-34
    - client configuration 14-18–14-30
    - command sequence tasks 14-17
    - flow control 14-15–14-16
    - IPSec and 14-16
    - packet sequencing 14-15
    - receive-window-size 14-15
    - support for L2TP clients 14-1
    - with IPSec transport mode 14-2
  - L2TP (setting) 14-7
  - label-switched paths (LSPs). *see* LSPs (label-switched paths)
  - label-switched routers (LSRs) *see* LSRs (label-switched routers)
  - LAC (L2TP access concentrator) 14-1
  - lac setting 14-7
  - LAN (local area network), VRs and VIs and 2-1
  - LANE (LAN emulation) 6-8
  - languages, proxies and, allowing or disallowing 13-25
  - LANs (local area networks), tying together 3-1
  - layer 2 transfer protocol (L2TP). *see* L2TP (layer 2 transfer protocol)
  - LCV alarm 4-3, 5-10
  - LDAP (lightweight directory access protocol)
    - plug proxies and 13-34
  - legacy Kanji, allowing or disallowing 13-25
  - length option 2-16
  - LES alarm 4-3, 5-10
  - level setting 7-14
  - Level-1 and Level-2 circuits
    - metrics and 9-14
    - PDU intervals and 9-13
  - Level-1 CSNPs, authenticating 9-10
  - Level-1 link-state PDUs, authenticating 9-10
  - Level-1 PSNPs, authenticating 9-10
  - Level-1, Level-2, and Level-1/Level-2 routers
    - avoiding sub-optimal routing paths 9-6
    - IS-IS and 9-15, 9-17
    - ISP VRs and 9-16
  - Level-2 CSNPs, authenticating 9-10
  - Level-2 link-state PDUs, authenticating 9-10
  - Level-2 PSNPs, authenticating 9-10
  - level-2-to-1-leaking setting 9-6
  - Level-x routers 9-8
  - LI (logical interfaces), VLANs and 3-7
  - lifetime rekey interval, changing 12-20
  - lifetimes, ISAKMP and SA 12-19
  - lightweight directory access protocol (LDAP). *see* LDAP (lightweight directory access protocol)
  - line code standards
    - alternate mark inversion 5-2
    - B8ZS 5-2
      - requirements 5-13
    - bipolar violations in AMI
    - clear channel capability 5-2, 5-13
    - pulse code modulation (PCM) 5-2
    - T1, DS3 and 5-9
  - line code violations
    - DS3 5-10
    - E3 4-3
    - OC-3 6-15
  - line errored seconds 6-15
    - DS3 5-10
    - E3 4-3
  - line failure counts 6-15
  - line loopbacks 4-5, 4-32, 5-8
  - line management formats 4-17, 5-20
    - DS3 and 5-20
  - line severely errored seconds 6-15
    - DS3 5-10
    - E3 4-3
  - line speed 6-26
  - line speed setting 2-20
  - line unavailable seconds 6-15

- link-state metric command 10-8
- Linux 1-2
  - PPTP and 13-55
- list (setting) 11-8
- list ID keyword 13-47, 13-48
- listen command 13-16
  - HTTP proxies and 13-23
  - plug proxies and 13-34
  - port numbers and 13-7
  - Telnet proxy 13-36
- LLC-encapsulation option 6-27
- LMI (local management interface)
  - see also* Frame Relay
  - commands 4-16–4-17, 5-19–5-20
    - intf-type 4-16, 5-19
    - LMI-N391DTE 4-16, 4-17, 5-19, 5-20
    - LMI-N392DCE 4-16, 5-19
    - LMI-N392DTE 4-16, 5-19
    - LMI-N393DTE 4-17, 5-20
    - LMI-T391DTE 4-16, 5-19
    - LMI-T392DCE 4-16, 5-19
    - LMI-T393DCE 4-16, 5-19
    - LMI-TYPE 4-17, 5-20
  - DCE and DTE interfaces
    - DCE error events 4-16, 5-19
    - polling interval timer 4-16, 5-19
    - status inquiries 4-16, 5-19
  - error threshold 4-16, 4-17, 5-19, 5-20
  - interface types 4-16, 5-19
  - line management formats 4-12, 4-17, 5-20
    - changing 4-17, 5-20
    - DLCIs and 4-17, 5-20
  - PVCs and 4-17, 5-20
  - types of 4-12, 5-15
  - unanswered status inquiries and 4-16, 5-19
- LMI revision 1 5-15
- LMI revision 1 line management format 4-12, 4-17, 5-20
- LMI-N391DTE command 5-19
  - using 4-17, 5-20
- LMI-N392DCE command 4-16, 5-19
- LMI-N392DTE command 4-16, 5-19
- LMI-N393DTE command 4-17, 5-20
- LMI-T391DTE command 4-16, 5-19
- LMI-T392DCE command 4-16, 5-19
- LMI-T393DCE command 4-16, 5-19
- LMI-TYPE command 4-17, 5-20
- lms admin-status drain setting 14-7
- lms admin-status enable command 14-13
- lms admin-status enable setting 14-7
- lms setting 14-7
- local commands 1-13
  - question mark (?) and 1-8, 1-14
- local management interface (LMI). *see* LMI (local management interface)
- local routes, exporting into BGP-4 8-2
- local VI (setting) 5-43
- local VIs. *see* VIs (virtual interfaces)
- local-address command
  - target command and 1-5
- local-domain setting 13-31
- local-isakmp-identity command keyword
  - abbreviation of 12-38
- local-ISAKMP-identity setting 12-25, 12-37
- local-pref in routing tables 7-37
- local-preference attribute (BGP-4), AS and 8-7
- local-secret-size setting 12-15
- log area packet setting 10-13
- logged command 13-19
  - HTTP proxies 13-24
  - recommendations 13-25
- logging command, SMTP proxies 13-31
- logging level, packets, and events
  - OSPF and 10-13
- logical interfaces 2-11, 6-31
  - essential criteria for 6-32
- logical setting 2-12
- login host protocol port 13-7
- logout command 1-11
- log-relay setting 13-31
- log-spam setting 13-31
- LOH (line overhead) 6-3, 6-38
- loop setting 6-7
- loopback (setting) 4-5, 4-32, 5-8
- loopback interfaces 2-3
  - control VRs and 1-25
  - creation of 2-3
  - DS3 5-8
  - in BGP update-source 8-20
  - IP addresses and 2-8
  - OC-3c, enabling 6-7
  - SAs and 12-40, 12-44
  - setting VI address 2-2
  - testing 4-5, 5-8
  - tunnel VIs and 12-46
  - types of 4-5, 4-32, 5-8
- loopback VI 1 2-2, 2-8
- loose keyword 11-7
  - explicit-path tunnels and 11-29
- Lotus Notes, plug proxies and 13-34
- LSAs (link-state advertisements)
  - LSDBs and 10-17
  - transmitting to neighbors 10-11
- LSDB refresh 9-13
- LSDBs
  - link metrics 10-8
  - LSAs and 10-17
- LSEs alarm 4-3, 5-10
- LSPs (label-switched paths)
  - advantages of 11-22
  - compared with PVCs 11-22

- LSPs (label-switched paths) (*continued*)
  - MPLS and 11-5
- LSPs (link-state PDU) 9-13, 9-16
- LSRs (label-switched routers) 11-22
  - forwarding processes of 11-23
  - MPLS and 11-5
- LTE (line terminating equipment)
  - OC-3 POS and 6-39
  - OC-3c and 6-3
  - OC-3c and SONET and 6-39
- M**
- M23 framing standard
  - p-bit path code violations 5-10
  - p-bit path errored seconds 5-10
  - p-bit path severely errored seconds 5-10
- M23 setting 5-7
- MAC addresses, ILMI and 6-8
- mail protocols. *see* POP3 proxies, SMTP (simple mail transfer protocol)
- mail-hub setting 13-31
- mailpoll command 13-30
- main-mode (crypto map flag value) 12-28
- managed device 2-21
- mask, subnet 1-5
- master control blades. *see* control blades 2-19
- match address setting 12-25, 12-30
  - ACLs and crypto maps and 12-29
- MATCH ADDRESS: Does not exist 12-68
- max-bytes setting 13-32
- max-conn setting
  - PPTP and 13-57
- maxhops setting 13-53
- maximum successive zeros rule 5-2
- max-key-len setting 12-15
- max-packet-size setting 6-5, 6-6
- max-recv setting 13-32
- max-retransmission setting 14-11
- max-retry-timer setting 12-14
- max-SA-count setting 12-15
- max-sessions-per-tunnel setting 14-8
- max-transport setting 5-43, 5-44
- max-tunnel setting 14-8
- maxvci-bits setting 6-10
  - VCCs and 6-12
- maxvc-number setting 6-10
- maxvpi-bits setting 6-9
  - allowable bit values 6-12
  - VCCs and 6-12
- maxvp-number setting 6-10
- MBS (maximum burst size) setting 6-21, 6-26
  - traffic descriptors and 6-23
- MCR (minimum cell rate) setting 6-18, 6-21, 6-26
- MD5 hashing algorithm, passwords and 10-12
- MD5 hashing, passwords and 8-10
- MD5. *see* authentication algorithms
- MED (multi-exit discriminator) 7-16, 8-17–8-18
  - AS and 8-7, 8-15
- MED (multi-exit-discriminator)
  - in routing tables 7-37
- medium-line-type setting
  - multi-mode fiber or single-mode fiber 6-7
- memory, flash
  - booting from 1-5
  - using 1-6, 1-8, 1-9
- meshes 8-20
- message send protocol port 13-7
- message transfer agents (MTAs). *see* SMTP (simple mail transfer protocol)
- messages 5-50
  - see also* specific messages
  - alarm, generating 5-9
  - alarms 5-10
  - event log
    - enabling 9-26
    - filtering 9-27
  - SNMP, type 2-23
  - traffic congestion, counting 4-19, 5-22
- metric (setting) 7-11, 9-14
- metric relative option 11-26
- metric setting, IS-IS routing and 9-4
- metrics, link, configuring 10-8
- metric-style setting 9-14
- met-type setting 7-14
- Microsoft ActiveX, allowing or disallowing 13-25
- Microsoft SQL/Sybase proxies 13-37
  - remote-port setting 13-38
  - remote-server setting 13-38
  - timeout setting 13-38
- MIME (multi-media Internet mail extension)
  - validating 13-31
- MIME-check setting 13-31
- MIPPPP, multilink session ID in RADIUS accounting 13-50
- mm-optical-fiber 6-7
- mode (setting) 12-23
- mode setting 14-32
- modes
  - config 1-13
    - show and 1-18
  - configuration, entering 1-12
  - show 1-13, 1-18
- Moy, John 10-1
- MPF (multi-part form), allowing or disallowing 13-25
- MPLS (multi-protocol label switching) traffic engineering 11-1–11-30
  - advantages of 11-21
  - Cisco HDLC encapsulation and 11-3
  - commands
    - CSPF and 11-5

- MPLS (multi-protocol label switching) traffic engineering
    - (continued)
    - commands
      - LSRs and LSPs and 11-5
    - configuring 11-2
      - basic configuration 11-3
      - notes 11-21–11-30
    - example 11-22
    - explicit paths 11-7
    - forwarding process 11-23
    - IGPs and 11-21
    - implementing with best-effort tunnels 11-24
    - links, overriding cost of 11-10
    - monitoring and troubleshooting 11-2, 11-17–11-21
      - ingress and egress points 11-18
      - interfaces 11-18
      - show mpls announced-route 11-17
      - show mpls cross-connect 11-18
      - show mpls interface 11-18
      - show mpls tunnel 11-18
      - show rsvp configuration 11-19
      - show rsvp interface 11-20
      - show rsvp session 11-20
    - over IS-IS 11-3
    - packets losses and 11-23
    - PPP encapsulation and 11-3
    - requirements 11-4
    - RSVP 11-19
      - activating 11-6
    - setting global attributes 11-6
    - settings
      - autoroute announce 11-4
      - autoroute metric 11-4
    - supported blade types 11-1
    - tunnel VIs and 11-9
    - tunnels. *see* MPLS tunnels
    - VI configuration 11-9–11-11
      - enabling 11-9
      - enabling RSVP 11-10
      - MPLS traffic-eng attribute-flags 11-11
      - router mpls 11-9
      - router rsvp 11-10
      - traffic-eng administrative-weight 11-10
    - voice over IP and 11-22
    - VR configuration 11-6–11-9
      - append-after 11-8
      - explicit-path 11-7
      - list 11-8
      - next-address 11-9
      - router mpls 11-6
      - router rsvp 11-6
      - traffic-eng enable 11-6
  - mpls traffic-eng administrative-weight setting 11-10
  - mpls traffic-eng attribute-flags setting 11-11
  - mpls traffic-eng setting
    - IGPs and 11-21
  - MPLS tunnels 11-11–11-17
    - see also* MPLS (multi-protocol label switching) traffic engineering
    - alternate 11-14
    - autoroute announce setting 11-12
    - autoroute metric setting 11-12
    - bandwidth setting 11-13
    - best effort 11-3, 11-13, 11-17, 11-24
    - Cisco IOS and 11-27
    - configuring 11-11
      - before activating 11-14
    - constrained shortest path first 11-3, 11-11
    - cost of 11-12
    - defining behavior of 11-26
    - destination setting 11-14
    - direction of 11-11
    - enable setting 11-14
    - example 11-26
    - explicit label-switched path 11-3
    - explicit path 11-27
    - explicit path example 11-29
    - path-option setting 11-14–11-17
    - recording actual route taken 11-16
    - record-route 11-16
    - subscriber VRs and 11-27
  - mpls-tunnel command 11-11
  - MSCHAPv1. *see* authentication algorithms
  - MTAs (message transfer agents). *see* SMTP (simple mail transfer protocol)
  - MTU (maximum transmission unit) 2-6
  - multiframe alignment, secure 5-3
  - multi-hop, enabling 14-7
  - multi-media Internet mail extension (MIME)
    - validating 13-31
  - multi-part form (MPF), allowing or disallowing 13-25
  - multiplexing, statistical 4-11
  - multi-protocol label switching (MPLS). *see* MPLS (multi-protocol label switching) traffic engineering
- ## N
- NAME (setting) 12-14
  - name resolution
    - BOOTP and DNS protocols
      - always-plain flag 12-28
  - name setting 12-30
  - names, VLAN subinterfaces, setting 3-8
  - NAT (network address translation)
    - access-lists requirement 13-47
    - address pools 13-46
    - configuring 13-44–13-46
    - obtaining help for 13-45
    - ending address setting 13-46

- NAT (network address translation) (*continued*)
  - ending port setting 13-46
  - ESP-based IPSec connections 12-4
  - in IPNOS 13-44
  - IP address pools and 13-46
  - ip nat list setting 13-45
    - example 13-48
    - list ID keyword 13-48
    - pool ID keyword 13-48
    - VI ID keyword 13-48
  - ip nat pool setting 13-45
    - example 13-46
    - poolID index number 13-46
    - starting and ending addresses 13-46
    - TCP/UDP port ranges 13-46
  - starting address setting 13-46
  - starting port setting 13-46
  - static
    - destination static keywords 13-49
    - example 13-49
    - ip nat inside command 13-48
    - using 13-48
  - transparent routing 13-44
  - unidirectional operation 13-44
- national bit (command) 4-7
- national bit (setting) 4-4
  - framing type and 4-5
- National Bureau of Standards (NIST) 12-6
- National Security Agency (NSA) 12-6
- navigation
  - config command 1-15
  - top command 1-16
  - up command 1-16
- neighbor command 8-3
  - configuring neighbors 8-8–8-13
  - E-BGP multihop 8-8
    - using 8-24
  - ebgp-multihop option 8-8
    - using 8-24
  - export-policy option 8-8
  - import and export policies and 8-13
  - import policies and 8-9
  - import-policy option 8-9
  - network command and 8-13
  - next-hop-self option 8-9
  - OSPF 10-13
  - passive option 8-10
  - password option 8-10
  - remote-AS option 8-11
  - shutdown option 8-11
  - timers option 8-12
  - update-source option 8-12, 8-18
  - viewing neighbor configuration 8-32
- neighbor setting 7-11
- neighbor-IP-address setting 6-10
- neighbor-name setting 6-10
- NEs (network elements), secondary fiber-optic connections and 6-37
- net (network entity title) setting
  - IPSX and 9-4
  - requirement for Cisco 9-4
- netBEUI 13-54
- netmask command 1-5
- NetMeeting proxies 13-39
  - netm-server command 13-41
  - remote desktop sharing 13-41
  - remote-port command 13-41
  - remote-port setting 13-41
  - remote-server setting 13-41
  - timeout setting 13-41
  - transparent mode 13-41
- Netscape 12-9
- network, control, OSPF and 1-25
- network address translation (NAT). *see* NAT (network address translation)
- network command, neighbor command and 8-13
- network news transfer protocol (NNTP). *see* NNTP (network news transfer protocol)
- networks
  - internal, IS-IS routing and 9-1
  - optical. *see* OC-3c, POS (Packet over SONET) 6-1
  - routed, VLANs and 3-1
  - switched, VLANs and 3-1
- new version of IPSX software, installing
- next-address setting 11-9
- next-hop-self option 8-9
- NIST (National Bureau of Standards) 12-6
- NMSs (network management systems) 2-21
  - IP addresses 2-23
  - SNMP host as 2-23
- NNIs (network-to-network interfaces) 4-11, 5-14
  - IPSX 9000 and 6-8
- NNTP (network news transfer protocol) 13-11
  - see also* plug proxies
  - plug proxies and 13-34
  - port 13-7
- no (keyword) 1-17
  - proper use of 1-17
- No alarms detected 5-10
- no func all command 13-21
- no ip ospf command 10-5
- no router ospf command 10-5
- no shutdown command 5-6
- no-advertise option 8-25, 8-26
- no-export option 8-25, 8-26
- no-export-sub option 8-25
- NONE (line management format) 4-17, 5-20
- Nortel Contivity
  - interoperability with IPSec 12-20
- note, explanation of xxi

- NRT-VBR (non-real-time variable bit rate) setting 6-18
  - service categories and 6-23
- NSA (National Security Agency) 12-6
- NSSAs (not-so-stubby areas)
  - configuring 10-6
  - example 10-14
  - OSPF support for 10-4
- numbers, slot
  - control VRs and 2-21
  - VRs and 2-4, 2-5
  
- O**
- Oakley extension 12-8
- OAM-continuity setting, receive-size setting and 6-30
- OAM-loopback setting 6-26
  - PCR (peak cell rate) setting and 6-30
- oc3 command 6-7
- oc-3 flag (command) 6-8
- OC-3 POS (packet over SONET)
  - see also* OC-3c
  - Cisco interoperability with 6-39
  - configuring 6-37–6-43
    - guidelines 6-37
  - encapsulation protocols 6-37
  - Frame Relay configuration 6-45
  - framing types 6-39
    - setting 6-40
  - LTE and PTE and 6-39
  - overhead channels 6-38
    - LOH 6-38
    - POH 6-38
    - SOH 6-38
  - path terminating equipment 6-39
  - PPP configuration
    - changing 6-43
    - maximum requests 6-44
    - PPP authentication types 6-44
    - PPP reauthentication period 6-44
    - PPP timeout value 6-44
    - settings 6-44
  - PPP encapsulation
    - configuring 6-43–6-45
  - PPP termination, maximum requests 6-44
  - SDH support 6-37
  - settings
    - crc 6-5, 6-6
    - max-packet-size 6-5, 6-6
  - SONET and SDH nomenclature 6-38
  - statistics
    - receive and transmit 6-41, 6-42
    - rx\_abort\_er 6-42
    - rx\_bytes and tx\_bytes 6-42
    - rx\_fcs\_er 6-42
    - rx\_frames and tx\_frames 6-42
- OC-3 POS (packet over SONET) (*continued*)
  - statistics
    - rx\_min\_er and rx\_max\_er 6-42
    - tx\_urun\_abt 6-43
    - tx\_user\_abt 6-43
    - viewing 6-40
  - STS 6-38
  - synchronous payload envelope (SPE) 6-38
  - synchronous transport module (STM-1) 6-38
  - tributary unit 6-38
  - unanswered PPP authentication results in disconnection 6-44
- OC-3c 6-1
  - see also* ATM (asynchronous transfer mode), OC-3 POS
  - alarms
    - enabling and disabling messages 6-6
  - ATM subinterfaces and 6-1
  - blades
    - accessing 6-3
    - configuring 6-3–6-8
    - operating as an LTE and a PTE 6-3
  - clock source, internal or line 6-5
  - commands
    - display stats 6-13
    - display stats sum 6-14
  - data, randomizing 6-6
  - defects 6-15
    - persistent 6-15
  - framing settings 6-5
  - IP addresses 6-10
  - loopback types 6-7
  - LTE 6-39
  - MPLS and 11-1
  - names 6-10
  - oc-3 flag command (J0 and framing) 6-8
  - performance counters. *see* performance counters
  - scrambling 6-6
  - settings
    - admin status 6-7
    - alarm 6-6
    - clock 6-5
    - crc 6-5, 6-6
    - framing 6-5
    - J0 6-6, 6-8
    - loop 6-7
    - max-packet-size 6-5, 6-6
    - medium-line-type 6-7
    - oper status 6-7
    - path-trace command 6-7
    - remote-path-trace 6-7
    - scramble 6-6
    - sonet and sdh options 6-5
  - statistics
    - alarm indication signals (AIS) 6-15
    - inhibition registers 6-15

- OC-3c (*continued*)
  - statistics
    - viewing 6-13
    - viewing most recent intervals 6-14
  - subinterfaces and 6-2
  - VCCs and 6-12
  - virtual channels and 6-1
  - virtual paths, addressing range 6-9
- old-CR-format flag 12-16
- old-DA-padding flag 12-16
- old-ID-in-hash flag 12-16
- old-message-padding flag 12-16
- old-payload-padding flag 12-16
- old-PK-encryption flag 12-16
- open shortest path first. *see* OSPF (open shortest path first)
- OpenView, HP, SNMP port settings and 2-23
- oper status setting, OC-3c 6-7
- operating status, Ethernet subinterfaces 3-9
- operating systems, acting as hosts for IPSX software 1-2
- operation and management (OAM). *see* ATM (asynchronous transfer mode)
- operation modes 1-13
- oper-status setting 2-20
- optical network support. *see* OC-3 POS (packet over SONET) 6-1
- origin (setting) 7-8
- OSPF (open shortest path first) 10-1–10-21
  - authentication
    - ip ospf authentication-key 10-12
    - ip ospf message-digest key 10-12
    - MD5 hashing algorithm 10-12
  - autonomous system border router (ASBR) 7-13
  - backbone 7-13
  - BGP and 7-11
  - checksum value 10-18
  - commands
    - default-cost keyword 10-4
    - display 10-19
    - ip ospf area 10-4
    - no ip ospf 10-5
    - no router ospf 10-5
    - ospf area 10-4
    - router ospf 10-3
    - show. *see* show command
    - stub area 10-5
  - configuring 10-2–10-13
    - area aggregate 10-13
    - area setting 10-5
    - as an ASBR 10-15
    - basic configuration 10-2
    - default cost setting 10-13
    - log area packet setting 10-13
    - notes 10-13
    - viewing configuration 10-3
  - default routes 10-7
- OSPF (open shortest path first) (*continued*)
  - disabling and deleting 10-5
  - DRs and BDRs 10-11
  - enabling 10-3
  - export policies 10-7, 10-13
  - external route tag setting for export policy 7-11
  - external type 1 routes 7-13, 10-17
  - external type 2 routes 7-13, 10-17
  - IETF routing protocol RFCs and 7-2
  - import and export policies and 7-3
  - link metrics 10-8
    - in the LSDB 10-8
    - link-state metric 10-8
  - link-state database in the VR OSPF display 10-17
  - logging levels, packets, and events 10-13
  - LSAs (link-state advertisements) in the LSDB 10-17
  - monitoring and troubleshooting 10-16–10-20
  - neighbors 10-13
  - NSSAs 10-6
    - support 10-4
  - passwords 10-12
  - priorities, ip ospf priority 10-11
  - recommended as control networks IGP 1-25
  - route filtering, subscriber VRs and ISP VRs 10-13
  - router IDs and 2-3
  - routers 10-3
    - area border 10-5
    - border 10-4
  - sequence number 10-18
  - settings
    - dead-interval 10-10
  - static routing 10-14
  - stub area 7-13
  - subscriber VRs and 7-35
  - summarization and filtering 10-7
    - area range 10-7
  - summary advertisements 10-4
  - timers 10-9
    - dead-interval 10-10
    - dead-interval timer 10-10
    - defining 10-9
    - hello-interval 10-10
    - retransmit-interval 10-11
    - transmit-delay 10-11
    - viewing settings 10-18
  - VIIs
    - cost command 10-8
    - enabling 10-4
  - ospf area command 10-4
  - ourname setting 13-24
  - outbound AH key setting 12-31
  - outbound AH SPI setting 12-31
  - outbound ESP authenticator setting 12-31
  - outbound ESP cipher setting 12-31
  - outbound ESP SPI setting 12-31

- outbound setting 13-9
  - overhead channels 6-3, 6-38
- ## P
- packet filters
    - see also* firewalls
    - ACLs and 13-5
      - reusing ACLs for other tasks 13-8
      - values in. *see* ACLs
    - creating 13-4
      - ACL setting 13-9
      - command syntax 13-9
      - deny setting 13-9
      - filter # setting 13-9
      - firewall setting 13-9
      - guidelines 13-10
      - inbound traffic setting 13-9
      - outbound traffic setting 13-9
      - permit setting 13-9
      - settings 13-9
    - design guidelines 13-2
    - dynamic
      - enabling 13-19, 13-22
      - FTP proxies and 13-19
    - filter ID number 13-10
    - firewall setting 13-6
    - guidelines 13-3
      - blank spaces between entries 13-4
      - blocking half a connection 13-4
      - default deny 13-4
      - routing decisions 13-4
    - port numbers and
      - example 13-7
    - priority of execution 13-3
    - proxy servers and 13-10
    - rule sets 13-3
    - use of ACLs with 13-10
    - VIs and 2-12
  - packet-filter command 13-9
  - packet-over-SONET. *see* OC-3 POS (packet over SONET)
  - packets
    - encapsulation types 6-26
    - IS-IS 9-16
    - losses of, reducing or eliminating 11-23
    - sizes 6-6
      - setting 5-45
    - VIs and 2-12
  - packet-sequencing setting 14-12
  - PAP (password authentication protocol). *see* authentication algorithms
  - passive option 8-10
  - passive setting 9-9
  - password option 8-10
  - password verification 1-5, 1-11
    - disabling 1-11
  - passwords
    - IS-IS 9-10
    - OSPF and 10-12
    - PPP and L2TP and 14-4
  - PAT (port address translation)
    - IPSec and 12-4
  - path code violations 6-16
  - path errored seconds 6-16
  - path failure counts 6-16
  - path severely errored seconds 6-16
  - path unavailable seconds 6-16
  - path-option setting 11-14–11-17
    - affinity option 11-16
    - bandwidth option 11-16
    - dynamic option 11-15
    - explicit path\_name option 11-15
  - paths
    - checking 6-7
    - dynamic
      - CSPF and 11-16
      - MPLS tunnels and 11-15
    - explicit, MPLS tunnels and 11-15
    - MPLS tunnels and, alternate 11-14
  - path-trace setting 6-7
    - string format 6-7
  - payload loopbacks 4-5, 5-8
  - p-bit path code violations 5-10
  - p-bit path errored seconds 5-10
  - p-bit path severely errored seconds 5-10
  - PCM (pulse code modulation) 5-2
  - PCR (peak cell rate) setting 6-18, 6-21, 6-28
    - OAM-loopback setting and 6-30
    - service categories and 6-26
    - traffic descriptors and 6-23
    - UBR traffic descriptor and 6-22
  - PCV alarm 5-10
  - PDUs (protocol data units)
    - authenticating 9-10
    - complete sequence number 9-16
      - intervals between sending 9-11, 9-13
    - control counters 9-22
    - IS-IS Hello 9-16
    - link-state 9-13, 9-16
      - enabling event logging 9-27
    - partial sequence number 9-13, 9-16
  - peer-AS setting 7-8, 7-11
  - perfect forward secrecy (PFS). *see* IPSec
  - performance counters
    - defects and failures 6-15
    - display stats command 6-13
    - line code violations (CV\_1) 6-15
    - line errored seconds (ES\_1) 6-15
    - line failure counts (FC\_1) 6-15

- performance counters (*continued*)
  - line severely errored seconds (SES\_l) 6-15
  - line unavailable seconds (UAS\_l) 6-15
  - path code violations (CV\_p) 6-16
  - path errored seconds (ES\_p) 6-16
  - path failure counts (FC\_p) 6-16
  - path severely errored seconds (SES\_p) 6-16
  - path unavailable seconds (UAS\_p) 6-16
  - section code violation (CV\_s) 6-15
  - section errored seconds (ES\_s) 6-15
  - section severely errored framing seconds (SEFS\_s) 6-15
  - section severely errored seconds (SES\_s) 6-15
- performance monitoring, DS3. *see* DS3
- permit keyword 13-47
- permit setting 13-9
- permit-bad-events settings 5-45
- persistent defects, OC-3c 6-15
- PES alarm 5-10
- PFS (crypto map flag value) 12-27
- PFS (perfect forward secrecy). *see* IPsec
- PFS-group setting 12-25, 12-37
- ping command 2-15
  - see also* traceroute command
  - abbreviations 2-16
  - ICMP requests and 2-16
  - ICMP timeout duration 2-16
  - maximum timeout value 2-17
  - packets
    - number of 2-16
    - options 2-16
    - size 2-16
    - TTL (time to live) 2-16
  - source IP address 2-16
  - syntax 2-16
  - verifying IPsec connections with 12-47
- PKI (public key infrastructure). *see* digital certificates
- plug proxies
  - automatic creation of LDAP, Lotus Notes, and NNTP 13-35
  - child-limit command 13-34
  - listen command and 13-34
  - Lotus Notes port setting 13-34
  - NNTP port setting 13-34
  - servers 13-11
- POH (path overhead) 6-3, 6-38
- point-to-point protocol. *see* PPP (point-to-point protocol)
- point-to-point tunneling protocol (PPTP). *see* PPTP (point-to-point tunneling protocol)
- policy routing. *see* export policies, import policies
- policy setting 13-16, 13-17
  - firewall access tables 13-13
  - HTTP proxies and 13-23
  - remote shells (rsh) 13-39
  - Telnet proxy 13-36
- pool ID keyword 13-48
- poolID setting 13-46
- POP3 port 13-7
- POP3 proxies 13-27
  - command examples 13-28
  - pop-server host name 13-28
  - port 110 and 13-27
  - servers 13-11
  - SMTP proxies and 13-28
- pop-server setting 13-28
- port (setting) 12-14
- port address translation (PAT)
  - IPsec and 12-4
- port command 1-5
- port numbers
  - listen command and 13-7
  - packet filters and
    - example 13-7
  - well known 13-7
- port setting
  - bootcfg 1-8
  - firewall access tables 13-13
  - SNMP 2-23
- ports, monitoring. *see* DS3, E3
- POS (packet over SONET). *see* OC-3 POS (packet over SONET)
- PPP (command level) 4-30
- PPP (point-to-point protocol)
  - see also* serial interfaces 4-10
  - as upper link layer protocol 4-20, 5-23
  - AUTH area and 4-30, 5-33
  - E3 and 4-10
  - encapsulation 4-35
    - MPLS and 11-3
    - unchannelized E3 and 4-30
  - encapsulation and 2-14
  - event logging 4-30, 5-33
  - in L2TP sessions 14-3
  - L2TP and 14-3
  - on unchannelized DS3 ports 5-38
  - on unchannelized E3 ports 4-35
  - over ATM. *see* PPPoATM (PPP over ATM)
  - over DLC channels, enabling or disabling 4-29, 5-32
  - over Frame Relay 5-27
    - authentication. *see* authentication algorithms
    - enabling or disabling 4-24, 5-28
    - reauthentication period 4-24, 5-28
    - retransmissions 4-24, 5-28
    - settings 4-24, 5-28
    - termination requests 4-24, 5-28
    - timeout value 4-24, 5-28
    - VIs and 4-25, 5-28
  - over HDLC channels 4-28–4-30, 5-31–5-33
    - reauthentication period 4-29, 5-32
    - retransmissions 4-29, 5-32
    - settings 4-29, 5-32

- PPP (point-to-point protocol) (*continued*)
  - over HDLC channels 4-28–4-30, 5-31–5-33
    - termination requests 4-29, 5-32
    - timeout value 4-29, 5-32
  - PPP command level 4-30, 5-33
  - provisioning 5-1
  - serial interfaces and 2-14
  - SONET/SDH links and 6-43
  - username database
    - example 14-4
    - LAC hostname 14-3
    - user names and passwords 14-4
- PPP (setting) 14-7
- PPP CLI command level 5-33
- PPPoATM (PPP over ATM) 6-26
  - see also* ATM subinterface configuration
  - configuring 6-33–6-37
    - commands for 6-34
  - disconnection timeout 6-36
  - DSL and DSLAM 6-33
  - enabling or disabling 6-36
  - help 6-35
  - packet encapsulation types and 6-26
  - reauthentication period 6-36
  - RFC 2364 6-34
  - settings
    - authentication 6-36
    - config-req-retransmit 6-36
    - enable 6-36
    - modifying 6-36
    - reauth 6-36
    - term-req-retransmit 6-36
    - timeout 6-36
- PPTP (point-to-point tunneling protocol) 13-54
  - see also* L2TP (layer 2 transfer protocol)
  - authentication setting 13-57
  - encryption and authentication, improving 13-58
  - encryption setting 13-57
  - idle-timeout setting 13-57
  - IP address pool 13-56
  - ip local pool setting 13-56
  - IP-pool setting 13-57
  - IPX/SPX 13-54
  - Linux support 13-55
  - max-conn setting 13-57
  - maximum connections 13-57
  - netBEUI 13-54
  - pap and 13-55
  - password systems 13-55
  - pptp server setting 13-56
  - PPTP setting 13-57
  - RADIUS and 13-55
  - servers, configuring 13-56
  - Windows NT support 13-55
  - pptp server setting 13-56
  - PPTP setting 13-57
  - preference setting 7-8
  - priority (setting) 9-9
  - private community strings, SNMP, defining 2-22
  - private key
    - in Diffie-Hellman 12-8
    - in digital certificates 12-9
  - processor blades
    - proxy servers on 13-11
    - specifying slot number 2-7
    - use in multiple-slot VRs 2-8
  - protocol (setting) 6-26, 7-6, 7-11
    - default value 6-34
    - packet filter value 13-6
  - protocol setting 4-20, 5-23
  - protocol types 6-27
  - protocols, authentication. *see* authentication algorithms
  - proxies
    - see also individual proxy types*
    - control blades and 13-11
  - proxy logging 13-22
  - proxy servers
    - address translation and 13-15
    - authentication servers and 13-11
    - child-limit setting 13-16, 13-23
    - control blades and 13-11
    - DNS servers and 13-11
    - firewall access tables and 13-12
    - FTP proxy. *see* FTP proxies
    - HTTP proxy. *see* HTTP proxies
    - listen command 13-16
    - on processor blades 13-11
    - packet filters and 13-10
    - plug proxy 13-11
    - policy setting 13-16
    - POP3 proxy 13-11
    - SMTP proxy 13-11
    - Telnet proxy 13-11
  - PSES alarm 5-10
  - psnp-interval setting 9-13
  - PSNPs (partial sequence number PDUs) 9-13, 9-16
  - PTE (path terminating equipment)
    - OC-3 POS and 6-39
    - OC-3c and 6-3
  - public community strings, SNMP, defining 2-22
  - public key infrastructure (PKI). *see* digital certificates
  - public key pairs, enabling generation of 12-68
  - put command 13-21
  - PVCs (permanent virtual channel circuits) 6-27
  - PVCs (permanent virtual circuits) 4-11, 5-14
    - see also* ATM (asynchronous transfer mode), Frame Relay
    - always-on connectivity and 6-2
    - compared with LSPs 11-22

- PVCs (permanent virtual circuits) (*continued*)
    - Frame Relay and 4-10, 5-14
    - information rate 4-11, 5-14
    - interface types and 4-15, 5-18
    - LMI settings and 4-17, 5-20
    - LMI type and 4-22, 5-25
    - OC-3c ATM 6-2
    - statistical multiplexing and 4-11
    - status and reports 4-12, 5-15
    - types of, ATM interfaces and 6-27
    - unchannelized DS3 and 5-38
    - unchannelized E3 and 4-35
  - PVC-type setting 6-27
  - PVCCs and 6-28
  - VCI setting and 6-30
- Q**
- Q933a line management format 4-17, 5-20
  - QoS (quality of service)
    - see also* ATM subinterface configuration
    - ACLs and 7-17
    - always-on connectivity and 6-2
    - available bit rate (ABR) 6-28
    - diff-serve and 7-17
    - diff-serve. *see* diff-serve
    - RSVP and 11-23
    - settings
      - available bit rate (ABR) 6-18
      - constant bit rate (CBR) 6-18
      - non-real-time variable bit rate (NRT-VBR) 6-18
      - real-time variable bit rate (RT-VBR) 6-18
      - unspecified bit rate (UBR) 6-18
    - traffic contracts 6-16
    - unspecified bit rate (UBR) 6-22
    - virtual channels and 6-16
    - virtual paths and channels and 6-16
  - qos command 7-26
  - question mark (?)
    - Ethernet commands and 2-19
    - Frame Relay commands and 4-25, 5-29
    - local commands and 1-8, 1-14
    - subinterfaces and 4-25, 5-29
  - quote of the day port 13-7
- R**
- RADIUS (remote authentication dial-in user service) 13-1, 13-49
    - for PPTP tunnel authentication 13-49
    - L2TP and 14-2
    - L2TP authentication and 14-2
    - radius-server list command 13-51
    - servers
      - types of 13-51
    - third-party support 13-49
  - RADIUS (remote authentication dial-in user service) (*continued*)
    - use of secret key 13-51
  - RADIUS servers
    - viewing status of 1-18
  - rate policing 4-21, 5-24
    - discard enable (DE) bit 4-21, 5-24
    - Frame Relay subinterfaces and 4-18, 5-21
    - oversubscription, managing 4-21, 5-24
  - rate-limit command
    - maximum data rate and 2-10
    - recommended setting 2-11
    - required arguments 2-10, 2-11
    - using 2-11
    - VI bandwidth and 8-16
  - rate-police command 4-13, 4-21, 5-16, 5-24
  - RBOCs (regional Bell operating companies)
    - Frame Relay networks, connecting 4-11, 5-14
  - reauth setting
    - authentication type and 5-28
    - DS3 5-28, 5-32
    - E3 4-24, 4-29
    - L2TP PPP 14-10
    - OC-3 POS 6-44
    - PPPoATM 6-36
  - reauthentication (PPP) 4-24, 4-29, 5-28, 5-32
    - authentication type and 5-28
  - reboot command 1-9
  - reboot now command 1-10
  - RECEIVED-BECN setting 4-19, 5-22
  - RECEIVED-FECN setting 4-19, 5-22
  - received-path-trace setting 6-7
  - Receiver has loss of frame 5-11
  - Receiver has loss of signal 5-10
  - Receiver has no alarms 5-11
  - Receiver has remote alarm 5-11
  - Receiver is getting AIS 5-10
  - Receiver is getting Idle 5-10
  - receive-SDU-size setting 6-27
  - receive-size setting, OAM-continuity setting and 6-30
  - receive-window-size setting 14-11, 14-12
  - record-route setting 11-16, 11-26
  - Redback Networks
    - manual key compatibility with CoSine 12-34
  - reference, explanation of xxi
  - related documentation xxii
  - relay-host list 13-33
  - relay-reject events
    - enabling and disabling 13-31
  - relay-reply setting 13-32
  - remote access, IPSX switches and 1-12
  - remote clients, enabling use of IPsec 12-26
  - remote desktop sharing, NetMeeting and 13-41
  - remote shells (rsh). *see* rsh (remote shells)
  - remote-AS option 8-11

- remote-path-trace setting 6-7
- remote-port setting
  - Microsoft SQL/Sybase proxies 13-38
  - NetMeeting proxies 13-41
- remote-server setting
  - Microsoft SQL/Sybase proxies 13-38
  - NetMeeting proxies 13-41
- remote shells (rsh) 13-39
- retransmission-timeout setting 14-11
- retransmit-interval setting 9-13, 10-11
- retransmit-throttle setting 9-14
- retry-limit setting 12-14
- retry-timer-sec setting 12-14
- retry-timer-usec setting 12-14
- reuse threshold 8-6
- RFC 1908 2-22
- RFC 2364 6-34
- RFCs. *see* IETF RFC entries
- RIP (routing information protocol)
  - commands
    - router rip 7-38
  - configuring 7-37–7-38
    - preliminaries 7-38
  - IETF routing protocol RFCs and 7-2
  - router rip command at VI level 7-37
  - subscriber VRs and 7-35
  - VI-level RIP settings 7-38
- RIP-2. *see* RIP (routing information protocol)
- RIP-IP setting 7-11
- RJ-11 6-33
- RO (read only) privileges 2-23
- route (setting) 4-21, 5-24, 5-50
  - for FRoIP DLCI 5-47, 5-50
    - example 5-49
- route coloring 8-25
- route filtering
  - between ISP VRs and subscriber VRs 10-13
  - community attributes and 8-27
  - export policies and 7-10
    - to control traffic volume 7-4
- route flapping, route summarization and 10-8
- route injection, BGP-4 and 8-3
- route reflection
  - advantages 8-23
  - IPSX switches and 8-20
  - route reflector client 8-3
  - VRs as clients 8-23
- route reflector clients, BGP-4 and 8-3
- route summarization
  - in OSPF 10-8
  - IS-IS 9-7
- routed networks, VLANs and 3-1
- route-flap dampening 8-5
- router isis command 9-3, 9-9
- router mpls setting 11-6, 11-9
- router ospf command 10-2, 10-3
- router rip command 7-37, 7-38
- router rsvp setting 11-6, 11-10
- routers
  - area border, OSPF and 10-5
  - border 10-4
  - Cisco CPE 10-13
  - core, diff-serve and 7-17
  - designated 9-9
  - ID 2-3
  - IS-IS, identifying 9-7
  - labels 2-3
  - levels 9-8
    - leaking 9-6
  - peer, verifying presence of 9-12
- routes, summary 10-4
- route-type setting
  - permissible values 7-13
- routing
  - see also* export policies, import policies
  - autonomous systems 7-35
  - default keyword 7-34
  - default routes 7-29
  - destination address and 7-4
  - IGPs and 7-35
  - loops, avoiding 7-36
  - metrics, IS-IS. *see* IS-IS routing
  - metrics in static routes 12-60
  - multiple default routes 7-34
  - protocols 7-2
    - ACLs and 7-4
    - common deployments 7-35
    - export policies and 7-3
    - exterior 8-1
    - interaction between 7-11
    - metrics in export policies 7-11
    - path selection criteria 7-36
    - QoS. *see* QoS (quality of service)
    - solving incompatible metrics 7-4
    - specifying a preferred route 7-8
    - supported AS numbers 7-35
  - static routes 7-29
    - uses for 7-31
  - sub-optimal paths, avoiding 9-6
  - tables
    - display route command 7-3
    - show ip route command 7-2
    - viewing 7-2
  - typical deployments 7-35
- routing information protocol (RIP). *see* RIP (routing information protocol)
- routing tables 10-8
- RSA (Rivest, Shamir, and Adelman) encryption 12-9, 12-19
- RSA algorithm, encryption module and 12-68

- rsh (remote shells)
    - proxies 13-38
      - policy setting 13-39
      - remote-server setting 13-39
    - security risks 13-39
  - RSOH (regenerator section overhead) 6-38
  - RSVP (resource reservation protocol) 11-1, 11-23
    - see also* MPLS (multi-protocol label switching) traffic engineering
    - hot spots and 11-23
    - MPLS and
      - sessions, viewing status of 11-20
      - viewing configuration 11-19
  - RT-VBR (real-time variable bit rate) setting 6-18
    - service categories and 6-23
    - voice over IP (VoIP) and 6-18
  - rules. *see* packet filters
  - RW (read/write) privileges 2-23
  - rx\_abort\_er POS statistic 6-42
  - rx\_fcs\_er POS statistic 6-42
  - rx\_max\_er POS statistic 6-42
  - rx\_min\_er POS statistic 6-42
  - rx-bytes POS statistic 6-42
  - rx-frames POS statistic 6-42
- ## S
- SA-per-host (crypto map flag value) 12-27
  - SA-per-net (crypto map flag value) 12-27
  - SA-per-port (crypto map flag value) 12-27
  - SA-per-protocol (crypto map flag value) 12-27
  - SAR (segmentation and reassembly) sublayer 6-17, 6-21
  - SAs (security associations) 12-45
    - characteristics 12-8
    - configuration notes 12-44
    - creating 12-39
      - advantages of loopback use 12-44
      - connecting at both ends 12-41
      - default 0.0.0.0 routes 12-47
      - ensure a reachable connection 12-40
      - loopback interface configuration 12-40
      - loopbacks as endpoints 12-44
      - tunnel interface configuration 12-42, 12-44
    - establishing with ACLs 12-28
    - failure, gateway lifetimes and 12-20
    - IKE 12-16
    - importance in IPSec connections 12-5
    - IPSec connections
      - creating 12-9
    - ISAKMP SA 12-8
    - lifetimes 12-19
      - rekey intervals 12-20
      - maximum number of 12-15
  - save command 1-8
  - savefile command 1-6
  - savefile setting 1-8
  - scaling 8-20
  - SCR (sustained cell rate) setting 6-21, 6-27
  - sdh (option) 6-5
  - SDH (synchronous digital hierarchy) 6-37
    - as an OC-3 POS framing type 6-40
    - framing, string size 6-7
    - regenerator section overhead (RSOH) 6-38
    - SONET and 6-38–6-39
    - STM-1 6-38
    - synchronous transport module (STM) 6-38
    - tributary units (TUs) 6-38
    - virtual container 3 6-38
  - SDUs (service data units) 6-27
  - secret key, RADIUS and 13-51
  - secret-recreate setting 12-14
  - section code violation 6-15
  - section errored seconds 6-15
  - section severely errored framing seconds 6-15
  - section severely errored seconds 6-15
  - section trace byte (J0) 6-6
  - secure connection settings (proposals). *see* IPSec
  - secure logins
    - see also* security
      - administrator login account 1-10
      - checkpasswd command and 1-5, 1-11
      - creating 1-10
      - enabling and disabling 1-11
      - sysuser command 1-10
  - secure multiframe alignment 5-3
  - secure shell (ssh), rsh and 13-39
  - security
    - see also* secure logins
    - ACLs and 7-7
    - community strings and 2-24
    - control VPNs and VRs and 1-26
    - customer networks and 2-19
    - NetMeeting and 13-41
    - randomized data and 6-6
    - rsh and 13-39
    - VRs and VIs and 2-2
  - security associations (SAs). *see* SAs (security associations)
  - security parameter index (SPI) numbers 12-7
  - security-association setting 12-37
  - SEFS alarm 4-3
  - SEFS\_s performance counter setting 6-15
  - Sendmail 13-29
  - serial interfaces
    - see also* DS3, E3, FRoIP (Frame Relay over IP)
    - configuring
      - viewing configuration 4-14, 5-17
    - DS3
      - authentication types 5-32
      - creating 5-17–5-21
    - E3, creating 4-14–4-18

- serial interfaces (*continued*)
  - eliminating need for 2-14
  - encapsulation types 4-14, 5-17
    - PPP 2-14
  - HDLC channels and 5-13
  - host channels and 4-14, 5-16
  - unchannelized DS3 and 5-35
- server setting 13-53
- servers
  - DNS, proxy servers and 13-11
  - SNMP, defining 2-22
  - TFTP, new boot images and 1-2
- service categories
  - cell rates and 6-21
  - for channels 6-16
  - selecting 6-24
  - traffic descriptors and 6-23
  - virtual paths and 6-18
- service provider networks, monitoring xxiii
- service provider VRs. *see* ISP VRs
- service-category setting 6-17, 6-22, 6-27
  - enable setting and 6-30
- service-VI setting 14-8
- SES\_l performance counter setting 6-15
- SES\_p performance counter setting 6-16
- SES\_s performance counter setting 6-15
- session keys
  - creating 12-31
  - inbound and outbound values 12-32
  - IPSec 12-2
- session submenu 14-8
- session-key setting 12-30
- set command
  - crypto map and 12-25
- setvalue setting 7-27
- severely errored framing seconds
  - E3 4-3
  - section 6-15
- severely errored seconds
  - c-bit path 5-10
  - line 5-10, 6-15
  - path 6-16
  - p-bit path 5-10
  - section 6-15
- SF (superframe format) 5-3
  - bit stuffing 5-7
- SHA-1. *see* authentication algorithms
- show blade command 3-2
- show command 1-18
  - at functional levels 1-13
  - at top CLI level 1-13
  - config command and 1-18, 9-6
  - DS3 and 5-4
  - IS-IS and, using 9-19
    - show isis adjacency 9-19
- show command (*continued*)
  - IS-IS and, using 9-19
    - show isis adj-log 9-19
    - show isis attributes 9-20
    - show isis circuit 9-21
    - show isis config 9-21
    - show isis database 9-22
    - show isis spf 9-24
    - show isis spf log 9-25
    - show isis statistics 9-26
  - MPLS and
    - show mpls announced-route 11-17
    - show mpls cross-connect 11-18
    - show mpls interface 11-18
    - show mpls tunnel 11-18
    - show rsvp configuration 11-19
    - show rsvp interface 11-20
    - show rsvp session 11-20
  - OSPF and, using 10-16-10-20
    - show ospf 10-16
    - show ospf area 10-16
    - show ospf attribute 10-16
    - show ospf configuration 10-17
    - show ospf database 10-17
    - show ospf interface 10-18
    - show ospf neighbor 10-19
  - show ip route command 7-2
  - show isis adjacency command 9-19
  - show isis adj-log command 9-19
  - show isis attributes command 9-20
  - show isis circuit command 9-21
  - show isis config command 9-21
  - show isis database command 9-22
  - show isis spf command 9-24
  - show isis spf log command 9-25
  - show isis statistics command 9-26
  - show mpls announced-route command 11-17
  - show mpls cross-connect command 11-18
  - show mpls interface command 11-18
  - show mpls tunnel command 11-18
  - show ospf area command 10-16
  - show ospf attribute command 10-16
  - show ospf command 10-16
  - show ospf configuration command 10-17
  - show ospf database command 10-17
  - show ospf interface command 10-18
  - show ospf neighbor command 10-19
  - show rsvp configuration command 11-19
  - show rsvp interface command 11-20
  - show rsvp session command 11-20
  - shutdown command 4-7, 4-32
    - commit command and 4-7, 5-5
    - disabling E3 interfaces with 4-4
  - shutdown option 8-11
  - signal label mismatch error 6-7

- signaling, MPLS. *see* MPLS (multi-protocol label switching) traffic engineering
- simple mail transfer protocol. *see* SMTP (simple mail transfer protocol)
- slot (setting) 2-7
- slot numbers 2-7
  - control VRs and 2-21
  - specifying 2-7
  - VRs and 2-4, 2-5, 2-7
- slots, sharing 2-8
- sm-optical-fiber 6-7
- SMTP (simple mail transfer protocol)
  - operation codes 13-29
  - port 13-7
  - proxies. *see* SMTP proxies
  - relay hosts 13-33
  - relay MTAs 13-33
  - server logging, syslogD and 13-31
- SMTP proxies
  - see also* SMTP (simple mail transfer protocol)
  - configuring 13-30
  - firewall access tables 13-28, 13-33
  - local-domain setting 13-31
  - logging command 13-31
  - mail-hub setting 13-31
  - maximum size of mail message 13-32
  - max-recv setting 13-32
  - MIME checking 13-31
  - policies, defining 13-30
  - policy requirements 13-29
  - POP3 proxies and 13-28
  - relay-host list 13-33
  - relay-reply setting 13-32
  - servers 13-11
  - spam logging 13-31
  - spam-host list 13-33
  - spam-reply setting 13-32
  - timeout setting 13-31
  - with syslogD 13-31
    - using the log-relay setting 13-31
- snmp (command) 2-22
- SNMP (simple mail transfer protocol)
  - community strings, public and private 2-22
- SNMP (simple network management protocol) 1-3
  - commit command and 2-22
  - community strings 2-24
  - configuration items and restrictions 2-22
  - control VR as SNMP agent 2-21
  - control VRs and 1-23, 2-21
  - defaults, checking 2-22
  - enabling 2-23
  - hosts
    - enabling 2-24
    - functioning as NMS 2-23
  - InVision and 2-22
  - SNMP (simple network management protocol) (*continued*)
    - IPSX as managed device 2-21
    - IPSX switch access blades 1-23
    - messages, enabling 2-23
    - MIB values
      - protecting 2-23
      - writing 2-23
    - NMS 2-21
    - RO and RW privileges 2-23
    - security 2-24
    - settings
      - IP-Address 2-23
      - port 2-23
      - SNMP-SERVER 2-23
      - type 2-23
      - traps host list 2-23
    - SNMP-SERVER setting 2-23
    - SNMPv1 and SNMPv2 messages, enabling 2-23
    - soft rekey 12-3
    - SOH (section overhead) 6-3, 6-38
    - Solaris (Sun) 1-2
    - sonet (option) 6-5
    - SONET (synchronous optical network)
      - as an OC-3 POS framing type 6-40
      - errors, signal label mismatch 6-7
      - European. *see* SDH (synchronous digital hierarchy)
      - frame capacity 6-20
      - line overhead (LOH) 6-3
      - LTE 6-3
      - OC-3c and LTE and 6-39
      - overhead channels 6-3
      - path overhead (POH) 6-3
      - PTE 6-3
      - SDH and 6-38–6-39
      - section overhead (SOH) 6-3
      - virtual tributary 6-38
    - source (option)
      - ping command 2-16
      - traceroute command 2-17
    - source (setting), firewall access tables 13-13
    - source addresses
      - ACLs 7-6
      - packet filter value 13-6
    - source ports
      - ACLs 7-6
      - packet filter value 13-6
    - spam
      - enabling or disabling logging of 13-31
      - listing email addresses of known perpetrators 13-33
    - spam-host list 13-33
    - spam-reply setting 13-32
    - speed option 4-9, 5-12
    - speed setting 3-4
    - SPEs (synchronous payload envelopes) 6-38

- SPF (shortest path first)
  - enabling event logging 9-27
  - interval between calculations 9-7
  - IS-IS and 9-1
  - viewing properties of 9-24
- spf-interval setting 9-7
- SPI (security parameter index) 12-33
  - numbers 12-7
- SPI-size setting 12-15
- srcaddr setting 7-6
  - diff-serve ACLs and 7-20
  - packet filter value 13-6
  - routing policies and 7-4
- srcport setting 7-6
  - packet filter value 13-6
- ssh (secure shell), rsh and 13-39
- standards, framing. *see* framing standards
- start address keyword 13-47
- starting address setting 13-46
- starting port setting 13-46
- startup
  - resuming after boot configuration 1-6
- state listing 2-10
- static NAT
  - destination static keywords 13-49
  - example 13-49
  - ip nat inside command 13-48
  - using 13-48
- static routes
  - see also* ip route command, IPsec
  - adding 7-29
  - configuring for IPsec 12-53
  - dual-homing 7-29
  - in subscriber VRs 7-35
  - ip route command 12-54, 12-57
  - ISP VRs and 12-64
  - metrics in 12-60
  - recommended uses 7-31
  - subscriber VRs and 12-63
- static routing
  - in combination with OSPF 10-14
- statistical bandwidth sharing
  - E3 and 4-11
- statistical multiplexing
  - Frame Relay and 4-11
- status
  - configuration, viewing 1-18
  - Ethernet interfaces 2-20
  - inquiries, Frame Relay 5-19
  - polling interval 4-17, 5-20
- status (setting) 3-4, 3-8, 13-53
- STM (synchronous transport module) 6-38
- strict keyword 11-7
- strings, community 2-24
  - community command and 2-24
- strings, community (*continued*)
  - snmp enable command and 2-24
  - SNMP hosts and 2-25
- STS (synchronous transport signal) 6-6, 6-38
- stub area command 10-5
- stub areas 10-5
  - area aggregate setting 10-13
  - default cost setting 10-13
- subinterfaces
  - see also* Frame Relay
  - bandwidth
    - assigning minimum 4-22, 5-25
    - of host HDLC channel and 4-22, 5-26
- Bc, Be, and CIR 4-21, 4-22, 5-24, 5-26
- commands
  - obtaining help for 4-25, 5-29
- configuring 4-18–4-23, 5-21–5-26
  - committed burst size (Bc) 4-20, 5-23
  - committed information rate (CIR) 4-20, 5-23
  - counters for congestion and dropped frames 4-19, 5-22
  - DLCI 4-20, 5-23
  - excess burst size (Be) 4-20, 5-23
  - PPP 4-20, 5-23
  - route 4-21, 5-24
  - traffic-rate policing 5-24
- DLCIs and 4-22
  - assigning 5-25
  - importance of 4-18, 5-21
- Ethernet
  - enabling 3-8
  - operating status 3-9
- OC-3c and 6-2
- packet encapsulation types 6-26
- point-to-point links and 4-21, 5-24
- PPP as higher-level protocol. *see* PPP (point-to-point protocol)
- rate policing and 4-18, 5-21
- settings 4-20, 5-23
  - Bc 4-20
  - Be 4-20
  - CIR 4-20
  - interface-DLCI 4-20
  - protocol 4-20
  - rate-police 4-21
  - route 4-21
- unchannelized DS3 5-37
  - DLCIs and 5-38
- unchannelized E3 4-34
  - DLCIs and 4-35
- VIs and 2-14
- VLANIDs and 3-6, 3-9
- VLANs and 3-10
  - communication points 3-7
  - naming 3-8

- subnet mask 1-5
- subnets, CIDR and 2-3
- subscriber networks
  - IGPs 7-31
- subscriber VRs 1-22, 1-23
  - access blades and 2-4, 2-5
  - BGP-4 and 8-3
  - control blades and 1-23
  - DHCP and 13-52
  - diff-serve rules 7-30
  - diff-serve rules and 7-19
  - dual-homing and multi-homing 2-2
  - example 7-33
  - failover capabilities 7-34
  - FRoIP and 5-41
  - import and export policies and 7-3
  - importance of assigning a slot number 2-4
  - IS-IS and 7-35, 9-15
  - ISP VRs and 1-22
  - MPLS tunnels and 11-27
  - OSPF and 7-35
  - RIP and 7-35
  - route filtering 10-13
  - routing protocols in 2-2
  - slot numbers
    - importance of 2-4, 2-5
  - static routes and 12-53, 12-63
  - typical services in 2-2
  - VIs and 3-6
  - VLANs and 3-10
- summary addresses 10-13
- summary-address setting 9-7
- Sun Solaris 1-2
- supernetting 2-3
- support, CoSine technical assistance xxiii
- switched networks
  - VLANs and 3-1
- switches. *see* IPSX switches
- switch-to setting 14-32
- symbols xxi
- syntax of commands
  - viewing 1-14
- syslogD 13-1, 13-41
  - enabling 13-43
  - facilities 13-42
  - levels 13-42
  - on the control blade 13-41
  - priorities 13-42
  - syslog.conf 13-41
  - with FTP proxy 13-22
  - with HTTP proxy 13-24
  - with proxies 13-41
  - with SMTP server logging 13-31
- system ID, IS-IS, viewing 9-6
- system-id setting 9-4, 9-7
- system-type setting 9-8
  - IS-IS routing and 9-4
- sysuser command
  - user login capabilities and 1-5
- T**
- T1
  - channel bank 5-3
  - configuring 5-9
  - DSOs and 5-2
    - combining 5-13
  - DSx and 5-3
  - EIs and 4-6
  - error checking 5-3
  - extended superframe format (ESF) 5-2, 5-3
  - facility data link 5-3
  - fractional, DSOs and 5-11
  - frame size 5-2
  - line code settings
    - DS3 and 5-9
  - viewing information on 5-8
- T1 ID (option) 5-12
- target command 1-5
  - local-address command and 1-5
- target setting 1-8
- TCP connection messages 8-18
- TCP/UDP ports
  - ACLs and 13-6
  - filtering 7-26
  - ranges 13-46
- technical assistance (CoSine) xxiii
- telecommunications providers
  - Frame Relay networks
    - connecting 4-11, 5-14
- Telnet port 13-7
- Telnet proxies
  - child-limit setting 13-36
  - examples 13-36
  - listen command 13-36
  - policy setting 13-36
  - servers 13-11
  - timeout setting 13-36
  - using 13-35
- terminal equipment synchronization 5-3
- term-req-retransmit setting
  - DS3 5-28, 5-32
  - E3 4-24, 4-29
  - L2TP PPP 14-10
  - OC-3 POS 6-44
  - PPPoATM 6-36
- test (setting) 4-5, 5-8
- TFTP
  - default gateway 1-5, 1-8
  - host IP address

- TFTP (*continued*)
  - hosts
    - HP-UX 1-2
    - IBM AIX 1-2
    - IP address 1-5, 1-8
    - Linux 1-2
    - Sun Solaris 1-2
    - Windows NT 1-2
  - location, modifying 1-5
  - operating systems and 1-2
  - subnet mask 1-5
- TFTP port 13-7
- threshold setting 13-53
- time slot option 4-9, 5-12
  - spaces and 4-10, 5-13
- timeout (setting)
  - DS3 5-28, 5-32
  - E3 4-24, 4-29
- timeout limits
  - during IPSX bootup 1-6
- timeout option 2-16
- timeout setting 13-19, 13-24
  - L2TP PPP 14-10
  - Microsoft SQL/Sybase proxies 13-38
  - NetMeeting proxies 13-41
  - OC-3 POS 6-44
  - PPPoATM 6-36
  - SMTP proxies 13-31
  - Telnet proxy 13-36
- timers option 8-12
- timers, OSPF 10-9
- TIs (tunnel interfaces). *see* tunnel interfaces
- token-hash-type setting 12-15
- top command 1-16
- TOS (type of service) setting 7-6
- traceroute command 2-15
  - see also* ping command
  - ending 2-18
  - for verifying IPsec tunnels 12-47
  - maximum number of hops 2-17
  - source IP address 2-17
  - syntax 2-17
  - verifying IPsec connections with 12-47
- traffic
  - AS and 8-15
  - channels and 5-11
  - conditioners, creating 7-17
  - congestion 4-11, 5-14
    - messages, counting 4-19, 5-22
  - contracts 6-16
  - controlling direction 8-15
  - customer, virtual channels 0 through 31 and 6-19
  - descriptors 6-21
    - service categories and 6-23
  - UBR 6-22
- traffic (*continued*)
  - DS3 and 5-8
  - E3 and 4-5
  - engineering. *see* MPLS (multi-protocol label switching) traffic engineering
  - hello intervals and 10-10
  - ILMI
    - importance of using default values 6-11
    - specifying virtual channel identifier for 6-10
    - specifying virtual path for 6-10
  - MPLS. *see* MPLS (multi-protocol label switching) traffic engineering
    - settings for 6-21
    - types, SONET and SDH and 6-37
    - volume, controlling 7-4
  - traffic-eng enable setting 11-6
  - traffic-rate policing. *see* rate policing
  - transforms, loading 12-25
  - transform-set setting 12-25, 12-30, 12-37
  - transmissions
    - data
      - DS3 and 5-2
    - voice 5-2
      - bandwidths 5-3
      - DS3 and 5-2
  - transmit-delay setting 10-11
  - transmit-queue-size setting 14-12
  - transmit-SDU-size setting 6-27
  - transmit-size setting, VPI setting and 6-30
  - transparency, IPsec and 12-2
  - transport (setting) 5-43
    - window-size option 5-43
  - transport modes, selecting. *see* IPsec
  - transport overhead 6-38
  - transports. *see* FRoIP (Frame Relay over IP)
  - traps
    - hosts, community strings and 2-25
    - SNMP, defining 2-22
  - triple-DES. *see* IPsec
  - TTL (time to live) option 2-16
  - tunnel (setting) 2-12
  - tunnel interfaces 2-11, 12-40
    - crypto maps and 12-44
    - SAs and 12-42, 12-44
    - testing with traceroute 12-47
  - tunnel setting 14-7
  - tunnel submenu 14-8
  - tunnel VIs
    - see also* IPsec, SA (security association)
    - IPsec
      - characteristics 12-45
      - subnet 12-45
    - local loopback specified as IPsec endpoint 12-46
    - MPLS and 11-9

### tunnels

- FRoIP 5-49
- IPSec. *see* FRoIPSec (Frame Relay over IPSec)
- mode, selecting. *see* IPSec
- MPLS. *see* MPLS tunnels

### tunnel-switch setting 14-7, 14-31

- TUs (tributary units) 6-38
- tx\_urun\_abt POS statistic 6-43
- tx\_user\_abt POS statistic 6-43
- tx-bytes POS statistic 6-42
- tx-frames POS statistic 6-42
- type setting, SNMP 2-23
- typographical conventions xxi

## U

### UAS\_1 performance counter setting 6-15

### UAS\_p performance counter setting 6-16

### UBR (unspecified bit rate) setting 6-18

### UBR setting 6-22

### UDP ports

- ACLs and 13-6
- AOL 13-37
- CompuServe 13-37
- monitoring 12-14

### unavailable seconds

- line 6-15
- path 6-16

### unchannelized DS3 5-1, 5-34

- accessing 5-35
- channel 0 5-36
- channel/subinterface 5-37
- configuring 5-35
- DLCI, CIR, Bc, and Be settings 5-38
- DLCIs and 5-38
- encapsulation at port level 5-36
- Frame Relay LMI settings 5-37
- Frame Relay over 5-36–5-38
- HDLC and 5-39
- interface serial command and 5-37
- OSI layer 2 protocol HDLC and 5-39
- PPP and 5-38
- PVCs and 5-38

### unchannelized E3

- channel 0 and 4-33
- channel/subinterface information 4-34
- Cisco interoperability and 4-7, 4-31
- config controller command and 4-31, 5-34
- disabling 4-32
- DLCI, CIR, Bc, and Be settings 4-35
- DLCIs and 4-35
- encapsulation at port level 4-33
- encapsulation formats and 4-32
- Frame Relay LMI settings and 4-34
- Frame Relay over 4-33–4-35

### unchannelized E3 (*continued*)

- FRoIP and 5-41
- HDLC and 4-36
- interface serial command and 4-34
- OSI layer 2 protocol HDLC and 4-36
- PPP and 4-30, 4-35
- PPP encapsulation 4-35
- PVCs and 4-35
- serial interfaces and 4-31
- settings 4-32
  - clock 4-32
  - framing 4-32
  - interface 4-32
  - loopback 4-32
- testing, loopback setting and 4-32
- UNI type (setting) 6-10
- UNI version (setting) 6-10
- UNIs (user-to-network interfaces) 4-11, 4-18, 5-14, 5-21
  - see also* ATM (asynchronous transfer mode)
  - IPSX 9000 and 6-8
  - settings
    - UNI type 6-10
    - UNI version 6-10

### UNIX syslog daemon. *see* syslogD

### up command 1-16

- VR creation and 2-6

### update-source option 8-12, 8-18

### user login capabilities

- enabling and disabling 1-5, 1-10, 1-11
- FTP, enabling 13-21

### user names, PPP and L2TP and 14-4

### userpriority setting 3-8

### use-zero-SPI flag 12-16

## V

### VC-3 (virtual container 3) 6-38

### VCCs (virtual channel circuits)

- configuring 6-12
- maximum number of 6-11

### VCI (setting) 6-28

- PVC-type setting and 6-30

### VC-multiplex-routed option 6-27

### VCS and VCIs (virtual channels and virtual channel

- identifiers) 6-2
  - 0 through 31 and customer traffic 6-19
  - 0 through 32 6-21
  - assigning 6-20
  - ATM QoS and 6-16
  - configuring 6-12
  - DLCIs and HDLC and 6-2
  - ILMI traffic
    - importance of using default values 6-11
    - specifying virtual channel identifier for 6-10
  - local VPIs and 6-19

- VCs and VCI (virtual channels and virtual channel identifiers) *(continued)*
  - OC-3c and 6-1, 6-10
  - service categories and 6-19
  - virtual paths and 6-11
- verbose option
  - show mpls tunnel command 11-18
  - show rsvp interface command 11-20
  - show rsvp session command 11-20
- Verisign 12-9
- vi command, IS-IS and 9-2
- VI ID keyword 13-47, 13-48
- virtual (setting) 2-12
- virtual circuits. *see* PVCs (permanent virtual circuits)
- VIs (virtual interfaces)
  - see also* VRs (virtual routers)
  - adding services to. requirements 2-2
  - ATM subinterfaces and 6-30
  - bandwidth, rate-limit command and 8-16
  - commands 2-9
    - connected-to. *see* connected-to command
    - crypto-map 2-9
    - ds-byte. *see* diff-serve
    - packet-filter 2-9
  - connecting 2-11–2-15
    - connected-to command 2-12
    - examples 2-12
    - testing connections 2-15, 2-17
    - types of connections 2-11, 2-14
  - control VPNs and 1-12
  - creating 2-3, 2-4–2-11
    - connected-to command 2-14
    - create command 2-6
    - IP addresses and 2-6
    - MTU and 2-6
    - prompt location and 2-6
    - with subinterfaces 2-14
  - diff-serve rules and 7-19
  - down state 6-32
  - enabling for OSPF 10-4
  - Ethernet blades and 3-5
  - Frame Relay and
    - bandwidth 4-13, 5-16
  - FRoIP and
    - identifying 5-43
  - Internet protocol security and. *see* IPSec
  - IS-IS routing and 9-2
  - IS-IS, defining 9-8
  - L2TP and 14-8
  - LANs and WANs and 2-1
  - local 5-43
    - see also* FRoIP (Frame Relay over IP)
    - creating 5-43
    - FRoIP and 5-41
  - loopback. *see* loopback interfaces
- VIs (virtual interfaces) *(continued)*
  - MPLS, enabling 11-9
  - packet filtering and 2-12
    - see also* packet filters 13-3
  - PPP and 4-25, 5-28
  - removing from VPN configuration 1-17
  - security strategies 1-26
  - settings
    - ip command and 2-9
    - viewing 2-8
  - state listing and 2-10
  - statistics, viewing 2-9
  - subscriber VRs and 3-6
  - troubleshooting, state listing and 2-10
  - VI 1
    - as loopback VI 2-2, 2-3, 2-8
    - default configuration 2-3
    - IP addresses and 2-4
  - viewing 2-9
  - viewing status of 1-18
  - VI-level RIP settings 7-38
  - VLANs and 3-9–3-12
  - VRs and 2-2, 3-7
- VLANID (setting) 3-8
- VLANIDs (virtual local area network identification numbers)
  - 3-6
    - subinterfaces and 3-9
    - VLANID setting 3-8
- vlanname setting 3-8
- VLANs (virtual local area networks) 3-1
  - advantages 3-1
  - connections
    - activating 3-11
  - Ethernet blades and 3-1, 3-2
    - number of 3-7
  - Ethernet subinterface configuration 3-7
  - IEEE 802.1Q compliance 3-1
  - LANs and 3-1
  - operating status 3-9
  - requirements 3-2
  - settings 3-8
    - status 3-8
    - userpriority 3-8
    - VLANID 3-8
    - vlanname 3-8
  - subscriber VRs and 3-10
  - switched networks and 3-1
  - VIs and 3-6, 3-9–3-12
    - Ethernet ports and 3-10
  - VLANIDs 3-6, 3-9
    - creating 3-8
- voice transmissions
  - bandwidths 5-3
  - DS3 and 5-2
  - pulse code modulation and 5-2

- VoIP (voice over IP) 6-18
    - MPLS and 11-22
  - VPCs, OC-3c and 6-12
  - VPI (setting) 6-28
    - transmit-size setting and 6-30
  - VPN (setting) 7-6, 12-14
  - VPNs (virtual private networks) 2-1
    - see also* control VPNs
    - connecting VIs across two VPNs 2-15
    - control blades and 1-23
    - IPSec and 12-2
    - IPSec-based, IPSX switches and 1-12
    - L2TP. *see* L2TP (layer 2 transfer protocol)
    - PPTP. *see* PPTP (point-to-point tunneling protocol)
    - VRs and 1-17, 2-2, 2-12
  - VPs and VPIs (virtual paths and virtual path identifiers) 6-2
    - see also* ATM (asynchronous transfer mode)
    - assigning 6-20
    - configuring 6-12
    - ILMI traffic
      - importance of using default values 6-11
      - specifying virtual path for 6-10
    - OC-3c 6-9
      - maximum number of 6-11
    - service categories and 6-18
    - VCI numbers and 6-19
    - virtual channels 0 through 31 and 6-19
    - virtual channels and 6-11
  - VR (setting) 7-6, 12-14
  - VR 165.165.100.100 2-21
  - VR 165.165.100.99 2-21
  - VR Access Policies 13-12
  - VRs (virtual routers)
    - see also* VIs (virtual interfaces)
    - access blades and 2-6
    - adding services to, requirements 2-2
    - before major configuration 1-20
    - BGP neighbor connections and 8-9
    - BGP-4 and 7-35
    - connecting 2-12
      - testing connections 2-15, 2-17
    - control VPNs and 1-24
    - control VRs. *see* control VRs
    - creating 2-4–2-11
      - create command 2-5
      - defining type 2-8
      - on multiple slots 2-7
      - VI 1 as loopback VI 2-2, 2-3, 2-8
    - DHCP and 13-52
    - import and export polices and 7-3, 8-13
    - interfaces in, TCP connection messages and 8-18
    - IS-IS, defining 9-8
    - ISP VRs. *see* ISP VRs
    - labels 2-2
    - LANs and WANs and 2-1
    - VRs (virtual routers) (*continued*)
      - local, viewing routing table for 7-3
      - processor blades and 2-8
        - in a multiple-slot VR 2-7
      - removing from VPN configuration 1-17
      - route reflection and 8-23
      - routing tables, checking 2-18
      - slot numbers 2-5
        - viewing 2-7
      - slot sharing 2-8
      - status, viewing 1-18
      - subscriber VRs. *see* subscriber VRs
      - types of 2-8
        - slots and 2-8
      - VIs and 3-7
        - minimum number of 2-2
        - viewing 2-9
      - VPNs and 1-17, 2-2
  - VTs (virtual tributaries) 6-38
- ## W
- wait command 1-6
    - usefulness of 1-7
  - WANs (wide-area networks)
    - IPSX switches and 1-12
    - VRs and VIs and 2-1
  - warning, explanation of xxi
  - watchdgenab command 1-6
  - watchdog timer 1-6
  - Web extensions
    - proxies and
      - allowing or disallowing 13-25
  - Web site, CoSine xxiii
  - well-known port numbers 13-7
  - whois port 13-7
  - window sizes, FRoIP settings 5-43
  - Windows 2000
    - IRE dial-up client and 12-35
    - L2TP and. *see* L2TP (layer 2 transfer protocol)
  - Windows 9x
    - IRE dial-up client and 12-35
  - Windows NT 1-2
    - IRE dial-up client and 12-35
    - PPTP and 13-55
  - window-size setting 5-40, 5-45
  - window-timeout setting 5-40, 5-45
- ## X
- X.509 digital certificates 12-8
  - X.509 distinguished name
    - for IPSec-dialup crypto maps 12-37
  - xauth. *see* authentication algorithms

## Y

yellow (command) 4-7

yellow detection and generation 5-9

